

Pixo Line Driver Multipower 600 White

Artikelnummer 0007865

SYLVANIA


PROTM



Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Constant current 350mA -1050mA LED in-track driver with GR6d-15 connector for LED light modules, polycarbonate body Clip holder and fixing screw included in the driver box, white finishing colour, max. system power: 56W, operating voltage: 220-240V / 50-60Hz Multipower driver module with various power settings meet all installation needs with one single product selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class I. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.672mmx32mmx31mm. This driver can be combined with Pixo Line 1500, and Pixo Line 900 (max.29W-600mA)

Technische Werte

Größe (mm)



Photometrie

Pixo Line Driver Multipower 600 White

Artikelnummer 0007865

SYLVANIA

Allgemeine Daten

Produktname	Pixo Line Driver Multipower 600 White
Technologie	Driver
Montage	Track mounting
Allgemeine Anwendungsbereiche	Hospitality, Museums & Galleries, Office, Retail
Umgebungstemperaturbereich	-20°C...+40°C
ETIM Klasse	EC002710
E-Nummer FI	4279415
Garantie	5 Jahre

Optische Daten

Lichtfarbe	N/A
Photobiological Risk Group	Not applicable

Elektrische Daten

Leistungsaufnahme gesamt (W)	56
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Leistungsfaktor der Lampe	0.95
THD (bei 230V, 50Hz, bei 100% Dimm-Level)	10
Elektrische Schutzklasse	Class I
Anzahl der Schaltzyklen vor vorzeitigem Ausfall	>100000
Dimmbar	No
Dimming method	N/A
Min. drive current (mA)	350
Max. drive current (mA)	1050
Drive current - Range (mA)	350mA / 1050mA
Einschaltstrom (A)	42
Dauer Einschaltstrom (µs)	168
Nennfrequenz (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Anzahl Leuchten pro 10A C Sicherung	15
Max. Anzahl Leuchten pro 16A C Sicherung	24
Max. Anzahl Leuchten pro 10A B Sicherung	9
Max. Anzahl Leuchten pro 16A B Sicherung	14
Überspannungsschutz (Differenzmodus --> L-N) (kV)	1

Physikalische Daten

Gehäusefarbe	White
IP Schutzart	IP20
IK Schutzart	IK03
Länge (mm)	672
Breite (mm)	31
Nominale Produkthöhe (mm)	31.5
Gewicht (kg)	0.36

Pixo Line Driver Multipower 600 White

Artikelnummer 0007865

SYLVANIA

Packaging

EAN Code	5410288078656
Einzelverpackung Länge (cm)	68.0
Einzelverpackung Breite (cm)	5.0
Einzelverpackung Tiefe (cm)	3.7
DUN 14 (außen)	15410288078653
Anzahl an Einheiten je Außenverpackung	20
Außenverpackung Länge (cm)	70.0
Außenverpackung Breite (cm)	27.0
Außenverpackung Tiefe (cm)	17.0

Safety data

Glühdrahttest (°C)	650
Optimale Betriebstemperatur (°C)	-20-40