

SylWork Inspection Mini

Artikelnummer 0090202

SYLVANIA

YourHome™



SylWork offers a range of high-performance LED work lights, available in both mains-powered and battery-operated models. Designed for ultimate flexibility, SylWork provides reliable, temporary lighting for a variety of DIY projects, including home decorating, household repairs, cleaning, tidying, and general maintenance tasks. The SylWork Inspection Mini is a portable, battery-operated inspection light, perfect for worksite tasks, camping, and outdoor activities. Its compact design makes it easy to carry, while the built-in hook allows for convenient hands-free use. The light is easily rechargeable with the included USB cable and features three-step dimming along with a flashing mode for emergency situations. Lightweight yet durable, it provides a practical lighting solution for various needs and comes with a three-year warranty. Ideal for both professional and home use.

Technische Werte

Photometrie

Allgemeine Daten

Produktname	SylWork Inspection Mini
Technologie	LED
Sockel	N/A
Gehäuse	ABS Plastic
Montage	Other
Integrierter Präsenzmelder	NONE
Allgemeine Anwendungsbereiche	Residential & Consumer
Umgebungstemperaturbereich	-10°C...+40°C
Virtual assistant compatibility	N/A
ETIM Klasse	EC000347
Garantie	3 Jahre

Optische Daten

Leuchtenlichtstrom (lm)	480
Farbtemperatur (K)	6500
Lichtfarbe	Cool White
Farbwiedergabeindex (Ra)	80
Farbkonsistenz (SDCM)	SDCM6
Ausstrahlungswinkel (°)	120
Distributionstyp	None
Photobiological Risk Group	RG1

SylWork Inspection Mini

Artikelnummer 0090202

SYLVANIA

Elektrische Daten

Notbeleuchtungstyp	
Leistungsaufnahme gesamt (W)	7.5
Elektrische Schutzklasse	Class III
Betriebsgerätetyp	Not required
Dimmbar	No
Dimming method	N/A
Energy Efficiency Class (A->G) of contained light source	F
Nennfrequenz (Hz)	DC

Lifetime data

Lebensdauer - L70B50	25000
----------------------	-------

Physikalische Daten

Gehäusefarbe	Black
IP Schutzart	IP54
IK Schutzart	IK06
Diffusor	Prismatic, Transparent
Diffusormaterial	PC Polycarbonate
Reflektoroberfläche	Not Applicable
Länge (mm)	337.5
Breite (mm)	30
Nominale Produkthöhe (mm)	30
Gewicht (kg)	0.192

Packaging

EAN Code	5410288902029
Einzelverpackung Länge (cm)	34.5
Einzelverpackung Breite (cm)	4.0
Einzelverpackung Tiefe (cm)	3.5
DUN 14 (außen)	15410288902026
Anzahl an Einheiten je Außenverpackung	40
Außenverpackung Länge (cm)	39.0
Außenverpackung Breite (cm)	19.5
Außenverpackung Tiefe (cm)	38.5

Safety data

Glühdrahttest (°C)	650
Optimale Betriebstemperatur (°C)	-10-40