

START Track Spot Integral 2700lm 930 MB WB BLK

Item No: 0005425


SYLVANIA



Integrated LED spotlight, Textured Black - RAL9005, simple and slick integral design with no driver box and without any visible screws, ideal for retail applications, die-cast aluminium body, passive cooling heatsink. Beam angle: 36°, additional lens 64° beam angle included, color temperature: 3000K, total system power: 32W, total fixture output: 2700 lm, LOR: 100%, colour rendering: Ra: 90 typical, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 800mA, electronic driver, non-dimmable, ultra low LED flickering rate (5% or less), power factor: >0.90, electrical protection: Class I, Global Track 3 Circuit GA69 adapter suitable for Global trac 3-circuit tracks, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 345°, vertical tilt: 90°, dimensions: Ø80x137x283, weight: 0.880kg.

Technical Assets


Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	0.32	0.32	36°	2625
1.0	0.63	0.63	36°	1313
1.5	0.95	0.95	36°	875
2.0	1.27	1.27	36°	656
2.5	1.59	1.59	36°	509
3.0	1.90	1.90	36°	417

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 36.2°)



START Track Spot Integral 2700lm 930 MB WB BLK

Item No: 0005425

SYLVANIA

General data

Product name	START Track Spot Integral 2700lm 930 MB WB BLK
Technology	LED
Housing	Aluminium
Mount	Track mounting
Environment	Indoor
General application	Retail
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4276968
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2700
Luminaire efficacy (lm/W)	85
Correlated colour temperature (k)	3000
Colour Code	930
Light colour	Warm White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	36
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	32
Supply current (A)	0.15
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Dimmable	No
Drive current (mA)	800
Inrush Current (A)	6.5
Inrush Duration (µs)	320
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	33
Max. products per 13A C Breaker	43
Max. products per 16A C Breaker	53
Max. products per 20A C Breaker	66
Max. products per 10A B Breaker	20
Max. products per 13A B Breaker	26
Max. products per 16A B Breaker	32
Max. products per 20A B Breaker	40

Lifetime data

Lifespan L70 B50	50000
Lifespan L80 B50	48100
Lifespan L80 B20	41000
Lifespan L80 B10	37700
Lifespan L90 B50	19500
Lifespan L90 B20	17000
Lifespan L90 B10	15900

START Track Spot Integral 2700lm 930 MB WB BLK

Item No: 0005425



Physical data

Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK03
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	283
Nominal Product Width (mm)	137
Nominal Product Height (mm)	80
Weight (kg)	0.88

Packaging

Product EAN number	5410288054254
Packaging single length / height (cm)	8.5
Packaging single width (cm)	8.5
Packaging single depth (cm)	28.5
DUN14 (inner)	15410288054251
Units per outer package	8
Packaging outer length / height (cm)	36.5
Packaging outer width (cm)	18.5
Packaging outer depth (cm)	30.5

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40