

SYLSPOT KIT ROUND 345LM 840 ADJ IP20 WHT 3-PACK

Item No: 0005732

SYLVANIA

General data

| | |
|----------------------------------|---|
| Product name | SYLSPOT KIT ROUND 345LM 840 ADJ IP20 WHT 3-PACK |
| Technology | LED |
| Cap/Base | N/A |
| Housing | PC Polycarbonate |
| Mount | Ceiling recessed mounting |
| Built in presence detector | NONE |
| Environment | Indoor |
| General application | Residential & Consumer |
| Operating temperature range (°C) | -10°C...+40°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC001744 |
| Warranty | 3 years |

Optical data

| | |
|-----------------------------------|---------------|
| Fixture luminous flux (lm) | 345 |
| Luminaire efficacy (lm/W) | 77 |
| Correlated colour temperature (k) | 4000 |
| Colour Code | 840 |
| Light colour | Neutral White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Beam Angle (°) | 36 |
| Distribution type | Symmetric |
| Photobiological Risk Group | RG1 |

Electrical data

| | |
|--|--------------------------------|
| Total power consumption (W) | 4.5 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Lamp power factor | 0.9 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 155 |
| Electrical protection | Class II |
| Control gear type | LED driver constant current |
| Dimmable | No |
| Dimming method | N/A |
| Inrush Current (A) | 10 |
| Inrush Duration (µs) | 150 |
| Energy Efficiency Class (A->G) of contained light source | G |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 100 |
| Max. products per 13A C Breaker | 130 |
| Max. products per 16A C Breaker | 160 |
| Max. products per 20A C Breaker | 200 |
| Max. products per 16A B Breaker | 160 |
| Connectable conductor cross section - Min (mm ²) | 0.75 |
| Connectable conductor cross section - Max (mm ²) | 1 |

Lifetime data

Lifespan L70 B50 | 15000

SYLSPOT KIT ROUND 345LM 840 ADJ IP20 WHT 3-PACK

Item No: 0005732



Physical data

| | |
|-------------------------------|----------------|
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK03 |
| Diffuser finish | Other |
| Diffuser material | None |
| Reflector finish | Not Applicable |
| Nominal Product Height (mm) | 85 |
| Nominal Product Diameter (mm) | 90 |
| Weight (kg) | 0.276 |

Packaging

| | |
|---------------------------------------|----------------|
| Product EAN number | 5410288057323 |
| Packaging single length / height (cm) | 9.0 |
| Packaging single width (cm) | 7.5 |
| Packaging single depth (cm) | 30.3 |
| DUN14 (inner) | 15410288057320 |
| Units per outer package | 16 |
| Packaging outer length / height (cm) | 38.5 |
| Packaging outer width (cm) | 32.7 |
| Packaging outer depth (cm) | 33.2 |

Safety data

| | |
|----------------------------------|--------|
| Glow Wire Test (°C) | 650 |
| Optimal operating condition (°C) | -10-40 |