

TOLEDO MICROLYNX FROSTED 470LM 830

Item No: 0026808

SYLVANIA



ToLEDo Microlynx LED is the perfect replacement for GX53 CFL lamp Compact design 15,000 hours rated life Higher lumen output Good colour rendering - CRI80 Non-dimmable 3 years warranty Perfect for kitchen cabinets, showcases, display units and wardrobes

Technical Assets

Photometrics

General data

Product name	TOLEDO MICROLYNX FROSTED 470LM 830
Technology	LED
Watt (Rated) (W)	5
Cap/Base	GX53
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740838
Warranty	3 years

Optical data

Useful luminous flux (Φ_{use})	470
Luminous flux (Rated) (lm)	470
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

TOLEDO MICROLYNX FROSTED 470LM 830

Item No: 0026808



Electrical data

Power consumption (W)	5
Wattage (W)	5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	2
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	208
Max. products per 16A C Breaker	334
Max. products per 20A C Breaker	418

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	74.3
Nominal Product Diameter (mm)	25
Weight (kg)	0.048

Packaging

Product EAN number	5410288268088
Packaging single length / height (cm)	7.6
Packaging single width (cm)	2.7
Packaging single depth (cm)	7.6
DUN14 (inner)	15410288268085
Units per inner package	6
DUN14 (outer)	25410288268082
Units per outer package	6
Packaging outer length / height (cm)	16.0
Packaging outer width (cm)	9.0
Packaging outer depth (cm)	8.4

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures