

# ToLEDo BALL V6 806LM 865 E14 SL

Item No: 0028346

**SYLVANIA**



- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent ball lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating

## Technical Assets

### Photometrics

#### General data

Product name	ToLEDo BALL V6 806LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740754
Warranty	3 years

#### Optical data

Useful luminous flux ( $\Phi_{use}$ )	806
Luminous flux (Rated) (lm)	806
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Beam Angle (°)	150
Lumen maintenance at end of nominal life (%)	70

# ToLEDo BALL V6 806LM 865 E14 SL

Item No: 0028346

**SYLVANIA**

## Electrical data

Power consumption (W)	8
Wattage (W)	8
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	2.7
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	131
Max. products per 16A C Breaker	211
Max. products per 20A C Breaker	364

## Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

## Physical data

Nominal Product Length (mm)	90
Nominal Product Diameter (mm)	45
Weight (kg)	0.045

## Packaging

Product EAN number	5410288283463
Packaging single length / height (cm)	4.5
Packaging single width (cm)	4.5
Packaging single depth (cm)	8.9
DUN14 (inner)	15410288283460
Units per inner package	6
DUN14 (outer)	25410288283467
Units per outer package	6
Packaging outer length / height (cm)	14.3
Packaging outer width (cm)	9.7
Packaging outer depth (cm)	8.5

## Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures