

ToLEDo Ball 806LM 827 E14 SL

Item No: 0029630


SYLVANIA



Compact and elegant design. Suitable replacement for halogen, incandescent and compact fluorescent lamps. Instant light at the flick of a switch. Uniform light distribution. Good colour rendering (CRI 80). Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas. Lower maintenance costs. 15,000 hours average rated life.

Technical Assets

Dimensions (mm)



Photometrics

ToLEDo Ball 806LM 827 E14 SL

Item No: 0029630

SYLVANIA

General data

Product name	ToLEDo Ball 806LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	6.5
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4741015
Warranty	3 years

Optical data

Useful luminous flux (Φ_{use})	806
Luminous flux (Rated) (lm)	806
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Power consumption (W)	6.5
Wattage (W)	6.5
Equivalent watt (W)	60
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Control gear required	No
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	2.8
Inrush Duration (μ s)	380
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	57
Max. products per 16A B Breaker	29

Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	82
Nominal Product Diameter (mm)	45
Weight (kg)	0.018

ToLEDo Ball 806LM 827 E14 SL

Item No: 0029630



Packaging

Product EAN number	5410288296302
Packaging single length / height (cm)	5.1
Packaging single width (cm)	5.1
Packaging single depth (cm)	9.5
DUN14 (inner)	15410288296309
Units per outer package	6
Packaging outer length / height (cm)	15.7
Packaging outer width (cm)	10.8
Packaging outer depth (cm)	10.5

Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures