

Sylvania Granit IP65 0-10V 26400lm 865 WB

Item No: 0039738

SYLVANIA


PROTM



Integrated LED highbay; Black aluminium housing; 26400lm; 165 W; 160 Lm/W; 6500K; Drive current: 720mA; CRI 80; 85° beam angle; 0-10V dimmable; IP65; IK08; Lifespan L80:B20 92,000 hrs; (D x H) 370 x 163 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.

Technical Assets


Dimensions (mm)



Photometrics

0.5	0.89	50°	6596
		50°	1488
1.0	1.78	50°	1739
		50°	399
1.5	2.67	50°	773
		50°	165
2.0	3.56	50°	480
		50°	95
2.5	4.45	50°	274
		50°	56
3.0	5.35	50°	193
		50°	47

Distance [m] Cone diameter [m]
C0 - C180 (half beam angle: 83.4°)



Sylvania Granit IP65 0-10V 26400lm 865 WB

Item No: 0039738



General data

Product name	Sylvania Granit IP65 0-10V 26400lm 865 WB
Technology	LED
Cap/Base	N/A
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
ETIM Class	EC001716
E-number FI	4357104
Warranty	5 years

Optical data

Fixture luminous flux (lm)	26400
Luminaire efficacy (lm/W)	160
Correlated colour temperature (k)	6500
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	165
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
No. Of switching cycles before premature failures	>100000
Dimmable	Yes
Dimming method	0-10V
Drive current (mA)	720
Inrush Current (A)	100
Inrush Duration (µs)	300
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	4
Max. products per 13A C Breaker	5
Max. products per 16A C Breaker	7
Max. products per 20A C Breaker	9
Max. products per 10A B Breaker	2
Max. products per 13A B Breaker	2
Max. products per 16A B Breaker	4
Max. products per 20A B Breaker	5
Mains surge immunity (differential mode -> L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B20	92000
Lifespan L90 B50	51000

Sylvania Granit IP65 0-10V 26400lm 865 WB

Item No: 0039738



Physical data

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Nominal Product Height (mm)	163
Nominal Product Diameter (mm)	370
Weight (kg)	2.703

Packaging

Product EAN number	5410288397382
Packaging single length / height (cm)	40.0
Packaging single width (cm)	40.0
Packaging single depth (cm)	14.5
DUN14 (inner)	05410288397382
Units per outer package	1
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	40.0
Packaging outer depth (cm)	14.5

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-30-50