

# Sylbay 4000K L2 9000LM AISLE DALI

Item No: 0040303


**SYLVANIA**



Logistics and Industry modular high bay luminaire with aisle optics to provide necessary illumination for narrow areas. Single body with 2 optical modules, 9100 lumens, 57W, 160lm/W, 4000K, CRI 80, aisle beam optic, DALI dimmable, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK08, (LxWxH) 410x386x133mm, Mains + control cable of 2 meter. Ball-impact-resistance according to VDE 0710-13 in suspended mounting mode.

## Technical Assets


### Dimensions (mm)



### Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.52 0.52	0.27 0.27	3500 1820 2000
1.0	1.04 0.63	0.27 0.27	1033 484 878
1.5	1.56 0.95	0.27 0.27	686 200 250
2.0	2.08 1.27	0.27 0.27	326 119 149
2.5	2.60 1.59	0.27 0.27	212 74 91
3.0	3.12 1.90	0.27 0.27	147 51 69

Distance [m]    Cone diameter [m]    Illuminance [lx]  
 — C0 - C180 (Half beam angle: 35.0°)  
 — C90 - C270 (Half beam angle: 55.0°)



# Sylbay 4000K L2 9000LM AISLE DALI

Item No: 0040303

**SYLVANIA**

## General data

Product name	Sylbay 4000K L2 9000LM AISLE DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-40°C...+50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001716
Warranty	5 years

## Optical data

Fixture luminous flux (lm)	9100
Luminaire efficacy (lm/W)	160
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	30*60
Glare control	< 19
Photobiological Risk Group	RG1

## Electrical data

Total power consumption (W)	57
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	5.1
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Control gear mounting	Integral
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	400
Inrush Current (A)	65
Inrush Duration (µs)	268
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	5
Max. products per 13A C Breaker	7
Max. products per 16A C Breaker	8
Max. products per 20A C Breaker	10
Max. products per 10A B Breaker	3
Max. products per 13A B Breaker	4
Max. products per 16A B Breaker	5
Max. products per 20A B Breaker	6

## Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B20	120000
Lifespan L90 B10	52000

# Sylbay 4000K L2 9000LM AISLE DALI

Item No: 0040303



## Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	410
Nominal Product Width (mm)	386
Nominal Product Height (mm)	133
Weight (kg)	5.03

## Packaging

Product EAN number	5410288403038
Packaging single length / height (cm)	60.0
Packaging single width (cm)	48.0
Packaging single depth (cm)	26.0
DUN14 (inner)	05410288403038
Units per outer package	1
Packaging outer length / height (cm)	60.0
Packaging outer width (cm)	48.0
Packaging outer depth (cm)	26.0

## Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-40-50