

START Panel UGR19 1200x300 3800Lm 840 SSA03

Item No: 0042689



General data

Product name	START Panel UGR19 1200x300 3800Lm 840 SSA03
Technology	LED
Cap/Base	N/A
Housing	Aluminium, Steel
Mount	Ceiling recessed mounting
Built in presence detector	PIR
General application	Education, Office
Operating temperature range (°C)	-10°C...+45°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
E-number FI	4170582
Warranty	5 years

Optical data

Fixture luminous flux (lm)	3800
Luminaire efficacy (lm/W)	106
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	36
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class II
Control gear required	Yes
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart Connected (SSA)
Minimum dimming level (%)	1
Drive current (mA)	750
Inrush Current (A)	30
Inrush Duration (µs)	175
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 13A C Breaker	27
Max. products per 16A C Breaker	33
Max. products per 20A C Breaker	42
Max. products per 10A B Breaker	12
Max. products per 13A B Breaker	16
Max. products per 16A B Breaker	20
Max. products per 20A B Breaker	25
Connectable conductor cross section - Max (mm²)	2.5

START Panel UGR19 1200x300 3800Lm 840 SSA03

Item No: 0042689



Lifetime data

Lifespan L70 B50	100000
Lifespan L70 B20	100000
Lifespan L70 B10	100000
Lifespan L80 B50	77000
Lifespan L80 B20	71000
Lifespan L80 B10	68000
Lifespan L90 B50	37000
Lifespan L90 B20	34000
Lifespan L90 B10	33000

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP40/20
IK rating	IK03
Diffuser finish	Prismatic
Diffuser material	Other
Nominal Product Length (mm)	1195
Nominal Product Width (mm)	295
Nominal Product Height (mm)	33
Weight (kg)	2.295

Packaging

Product EAN number	5410288426891
Packaging single length / height (cm)	39.5
Packaging single width (cm)	123.5
Packaging single depth (cm)	8.5
DUN14 (inner)	15410288426898
Units per outer package	2
Packaging outer length / height (cm)	125.0
Packaging outer width (cm)	19.0
Packaging outer depth (cm)	41.5

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-10-45