

START Surface IP54 MW 500-2000lm 830/840

Item No: 0043406

SYLVANIA


STARTTM



Ceiling / wall luminaire with integrated LED. Perfect solution for hallways, circulation spaces or foyers. Body Size diameter 300mm. Besa mounting box compatible, hole distance 51 & 78mm. DualTone functionality enables switch between 3000K and 4000K colour temperatures. With the help of DIP Switch multiple lumen outputs can be set up in 4 steps (4000K: 6W 500lm, 9.3W 1000lm, 13.5W 1500lm, 17.5W 2000lm). Efficacy up to 114lm/W. Supplied with integrated Microwave sensor for automatic on-off presence control. Non-dimmable. IK03, IP54. Low maintenance with lifespan 120,000 hours L70:B50.

Technical Assets


Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Illuminance [lx]
0.5	1.72 1.70	50° 50°	50° 50°	400 400
1.0	3.44 3.56	50° 50°	50° 50°	100 100
1.5	5.15 5.35	50° 50°	50° 50°	44 44
2.0	6.87 7.13	50° 50°	50° 50°	33 33
2.5	8.59 8.91	50° 50°	50° 50°	26 26
3.0	10.31 10.69	50° 50°	50° 50°	22 22

Distance [m] Cone diameter [m]
— C2 - C180 (half beam angle: 121.4°)
— C90 - C270 (half beam angle: 119.6°)



START Surface IP54 MW 500-2000lm 830/840

Item No: 0043406

SYLVANIA

General data

Product name	START Surface IP54 MW 500-2000lm 830/840
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Built in presence detector	MICROWAVE
General application	Museums & Galleries, Hospitality
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A, Amazon Alexa
ETIM Class	EC002892
E-number FI	4279505
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2000
Luminaire efficacy (lm/W)	114
Light colour	Warm White or Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Distribution type	Symmetric
Photobiological Risk Group	RG1

Electrical data

Emergency type	
Total power consumption (W)	17.5
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.8
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class II
Control gear type	LED driver constant current
No. Of switching cycles before premature failures	>100000
Dimmable	No
Dimming method	N/A
Drive current (mA)	100
Inrush Current (A)	3
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	72
Max. products per 13A C Breaker	93
Max. products per 16A C Breaker	117
Max. products per 20A C Breaker	143
Max. products per 10A B Breaker	43
Max. products per 13A B Breaker	56
Max. products per 16A B Breaker	69
Max. products per 20A B Breaker	86
Connectable conductor cross section - Max (mm²)	1.5

START Surface IP54 MW 500-2000lm 830/840

Item No: 0043406



Lifetime data

Lifespan L70 B50	120000
Lifespan L70 B20	120000
Lifespan L70 B10	120000
Lifespan L80 B50	105000
Lifespan L80 B20	95000
Lifespan L80 B10	89000
Lifespan L90 B50	51000
Lifespan L90 B20	47000
Lifespan L90 B10	44000

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP54
IK rating	IK03
Diffuser finish	Opal
Diffuser material	PMMA Acrylic
Nominal Product Height (mm)	94
Nominal Product Diameter (mm)	300
Weight (kg)	0.577

Packaging

Product EAN number	5410288434063
Packaging single length / height (cm)	32.4
Packaging single width (cm)	10.1
Packaging single depth (cm)	32.4
DUN14 (inner)	15410288434060
Units per outer package	6
Packaging outer length / height (cm)	63.1
Packaging outer width (cm)	33.9
Packaging outer depth (cm)	34.4

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-20-40