


START WATERPROOF 1500 HOUSING 1X

Item No: 0047195

SYLVANIA


STARTTM



- Luminaire, polycarbonate housing
- Single version, 1500mm
- Protection type IP65
- Luminous flux and light colour vary depending on LED tubes used
- To be used with T8 LED tubes
- Easy to install with stainless steel fixing brackets included for ceiling mounting
- Ideal for any industrial facilities, garages, car parks, workshops.

Technical Assets

Dimensions (mm)



Photometrics

START WATERPROOF 1500 HOUSING 1X

Item No: 0047195

SYLVANIA

General data

Product name	START WATERPROOF 1500 HOUSING 1X
Technology	Light Source Not Integrated
Cap/Base	G13
Housing	PC Polycarbonate
Mount	Wall surface mounted
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
E-number FI	4357157
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1
Luminaire efficacy (lm/W)	1
Light colour	N/A
Colour Variation Initial (SDCM)	N/A
Distribution type	Symmetric
Photobiological Risk Group	Not applicable

Electrical data

Light source included	Fixture without Lightsource
Emergency type	
Total power consumption (W)	0.1
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class II
Control gear type	Not required
Dimmable	No
Dimming method	N/A
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	1
Max. products per 16A C Breaker	1
Max. products per 16A B Breaker	1
Connectable conductor cross section - Max (mm ²)	1.5

Lifetime data

Lifespan L70 B50	25000
------------------	-------

Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1580
Nominal Product Width (mm)	65
Nominal Product Height (mm)	60
Weight (kg)	0.8

START WATERPROOF 1500 HOUSING 1X

Item No: 0047195



Packaging

Product EAN number	5410288471952
Packaging single length / height (cm)	163.5
Packaging single width (cm)	6.4
Packaging single depth (cm)	4.5
DUN14 (inner)	15410288471959
Units per outer package	12
Packaging outer length / height (cm)	165.0
Packaging outer width (cm)	15.9
Packaging outer depth (cm)	28.4

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40