


RANA NEO 3700LM REC 1250x310 840 CC EM 1L WHITE

Item No: 0052609

SYLVANIA


PROTM



Ceiling Recessed LED Linear luminaire (lay-in), with Louvre + MPO diffuser, Direct Light Distribution, Luminaire Dimensions: 1246x308x52mm, Sylvania White body colour, IP20, IK07, Emergency 3 hours, Low LED flicker (+/-5%), Neutral White (4000K), LED Colour Temperature, 3761lm, 32W, 117lm/W, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<18, Luminance at 65° < 3000 cd/m2, Lifespan: 96,000 hours L80B20, Glow Wire Test 850°C, Quick and easy electrical connection with direct access to push-connectors on top, 2 x metallic safety cables (1.5m) included, the luminaire can be covered with building insulation of Glass Wool type.

Technical Assets

Dimensions (mm)




Photometrics

0.5	0.91 0.69	S/D S/CB S/CO	9570 42.4° 34.8°	1901 2573
1.0	1.83 1.38	S/D S/CB S/CO	2380 42.4° 34.8°	480 680
1.5	2.74 2.07	S/D S/CB S/CO	1083 42.4° 34.8°	239 331
2.0	3.65 2.76	S/D S/CB S/CO	596 42.4° 34.8°	133 181
2.5	4.57 3.45	S/D S/CB S/CO	393 42.4° 34.8°	77 107
3.0	5.48 4.14	S/D S/CB S/CO	296 42.4° 34.8°	54 74

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (half beam angle: 69.2°)
— C90 - C270 (half beam angle: 84.9°)



RANA NEO 3700LM REC 1250x310 840 CC EM 1L WHITE

Item No: 0052609

SYLVANIA

General data

Product name	RANA NEO 3700LM REC 1250x310 840 CC EM 1L WHITE
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Built in presence detector	NONE
General application	Office, Education
Operating temperature range (°C)	5°C...+25°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	3761
Luminaire efficacy (lm/W)	117
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	80

Electrical data

Emergency mode	Non-maintained
Emergency type	
Emergency duration (h)	3
Total power consumption (W)	32
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.97
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	15
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	300
Inrush Current (A)	5.5
Inrush Duration (µs)	20
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	41
Max. products per 13A C Breaker	53
Max. products per 16A C Breaker	65
Max. products per 20A C Breaker	82
Max. products per 10A B Breaker	41
Max. products per 13A B Breaker	53
Max. products per 16A B Breaker	65
Max. products per 20A B Breaker	82
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	2.5

RANA NEO 3700LM REC 1250x310 840 CC EM 1L WHITE

Item No: 0052609



Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	96000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	Not Applicable
Nominal Product Length (mm)	1246
Nominal Product Width (mm)	308
Nominal Product Height (mm)	51
Weight (kg)	5.6

Packaging

Product EAN number	5410288526096
Packaging single length / height (cm)	139.0
Packaging single width (cm)	37.0
Packaging single depth (cm)	9.5
DUN14 (inner)	05410288526096
Units per outer package	1
Packaging outer length / height (cm)	139.0
Packaging outer width (cm)	37.0
Packaging outer depth (cm)	9.5

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	5-25