

START Waterproof Twin 1200 IP65 4800lm 865

Item No: 0067964


SYLVANIA



Start Waterproof, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing, Polycarbonate diffuser, 4800 lm, 40 W, 127 lm/W, 6500 K, drive current 1050 mA, non dimmable, CRI80, IP65, IK08, Class I, nominal average lifetime (h): 50000, 1278 mm x 110 mm x 78 mm, energy class: A++ A+ A, D-mark

Technical Assets


Dimensions (mm)



Photometrics

| Distance [m] | Cone diameter [m] | Beam diameter [m] | Beam diameter [m] | Illuminance [lx] |
|--------------|-------------------|-------------------|-------------------|--------------------|
| 0.5 | 1.20 1.46 | 0.07 | 0.07 | 5431 530 554 |
| 1.0 | 2.41 2.91 | 0.07 | 0.07 | 1688 270 156 |
| 1.5 | 3.61 4.37 | 0.07 | 0.07 | 715 330 85 |
| 2.0 | 4.82 5.82 | 0.07 | 0.07 | 422 330 117 |
| 2.5 | 6.02 7.28 | 0.07 | 0.07 | 287 330 117 |
| 3.0 | 7.23 8.73 | 0.07 | 0.07 | 179 330 117 |

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 111.0°)
 — C90 - C270 (Half beam angle: 100.0°)



START Waterproof Twin 1200 IP65 4800lm 865

Item No: 0067964

SYLVANIA

General data

| | |
|---|--|
| Product name | START Waterproof Twin 1200 IP65 4800lm 865 |
| Technology | LED |
| Housing | PC Polycarbonate |
| Mount | Ceiling surface mounting |
| Fixture rating | Enclosed |
| General application | Logistics & Industry |
| Operating temperature range (°C) | -20°C...+40°C |
| Performance ambient temperature Tq (°C) | 25 |
| ETIM Class | EC002892 |
| E-number FI | 4309082 |
| Warranty | 5 years |

Optical data

| | |
|-----------------------------------|----------|
| Fixture luminous flux (lm) | 4800 |
| Luminaire efficacy (lm/W) | 120 |
| Correlated colour temperature (k) | 6500 |
| Light colour | Daylight |
| CRI (Ra) | 80 |
| Glare control | < 25 |
| Photobiological Risk Group | RG1 |

Electrical data

| | |
|--|-----------------------------|
| Total power consumption (W) | 40 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Lamp power factor | 0.95 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 20 |
| Electrical protection | Class I |
| Control gear required | No |
| Control gear type | LED driver constant current |
| Dimmable | No |
| Dimming method | N/A |
| Drive current (mA) | 1050 |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 20 |
| Max. products per 13A C Breaker | 30 |
| Max. products per 16A C Breaker | 40 |
| Max. products per 20A C Breaker | 50 |
| Max. products per 10A B Breaker | 16 |
| Max. products per 13A B Breaker | 24 |
| Max. products per 16A B Breaker | 32 |
| Max. products per 20A B Breaker | 40 |

Lifetime data

| | |
|------------------|-------|
| Lifespan L70 B50 | 60000 |
| Lifespan L70 B20 | 60000 |
| Lifespan L70 B10 | 60000 |
| Lifespan L80 B50 | 60000 |
| Lifespan L80 B20 | 60000 |
| Lifespan L80 B10 | 60000 |
| Lifespan L90 B50 | 59000 |
| Lifespan L90 B20 | 53000 |
| Lifespan L90 B10 | 50000 |

START Waterproof Twin 1200 IP65 4800lm 865

Item No: 0067964

SYLVANIA

Physical data

| | |
|-----------------------------|------------------|
| Housing colour | Grey |
| IP rating | IP65 |
| IK rating | IK08 |
| Diffuser finish | Transparent |
| Diffuser material | PC Polycarbonate |
| Nominal Product Length (mm) | 1278 |
| Nominal Product Width (mm) | 110 |
| Nominal Product Height (mm) | 78 |
| Weight (kg) | 1.82 |

Packaging

| | |
|---------------------------------------|----------------|
| Product EAN number | 5410288679648 |
| Packaging single length / height (cm) | 137.2 |
| Packaging single width (cm) | 11.6 |
| Packaging single depth (cm) | 8.4 |
| DUN14 (inner) | 05410288679648 |
| Units per outer package | 1 |
| Packaging outer length / height (cm) | 137.2 |
| Packaging outer width (cm) | 11.6 |
| Packaging outer depth (cm) | 8.4 |

Safety data

| | |
|----------------------------------|--------|
| Glow Wire Test (°C) | 850 |
| Optimal operating condition (°C) | -20-40 |
| Dry applications use only | No |