

SylCabinet 75LM TriTone

Item No: 0090115

SYLVANIA


YourHome™



LED portable cabinet light with rechargeable lithium battery and PIR motion sensor developed for various applications, including closets, wardrobes, kitchen cabinets or working spaces. Adjustable colour temperatures: Warm white (3000K), Cool white (4000K) and Daylight (5500K), with ultra thin design in 250 mm length. Available in 75 lumen. Low maintenance with 25,000 hour LED life expectancy.

Technical Assets

Dimensions (mm)



Photometrics

General data

| | |
|----------------------------------|-------------------------|
| Product name | SylCabinet 75LM TriTone |
| Technology | LED |
| Built in presence detector | PIR |
| General application | Residential & Consumer |
| Operating temperature range (°C) | 0°C...+40°C |
| ETIM Class | EC000347 |
| Warranty | 3 years |

Optical data

| | |
|--|---|
| Fixture luminous flux (lm) | 75 |
| Luminaire efficacy (lm/W) | 75 |
| Ambient temperature for maximum luminous flux (°C) | 25 |
| Light colour | Warm White or Neutral White or Daylight |
| CRI (Ra) | 80 |
| Beam Angle (°) | 120 |
| Photobiological Risk Group | RG1 |

SylCabinet 75LM TriTone

Item No: 0090115



Electrical data

| | |
|--|-------------|
| Emergency type | |
| Total power consumption (W) | 3.5 |
| Primary Supply/Product voltage - min (V) | 5.0 |
| Primary Supply/Product voltage - max (V) | 5.0 |
| Electrical protection | Class III |
| Dimmable | Yes |
| Dimming method | Onboard pot |
| Minimum dimming level (%) | 10 |
| Energy Efficiency Class (A->G) of contained light source | C |
| Nominal Frequency (Hz) | DC |

Physical data

| | |
|-----------------------------|-------|
| IP rating | IP20 |
| IK rating | IK03 |
| Nominal Product Length (mm) | 250 |
| Nominal Product Width (mm) | 38 |
| Nominal Product Height (mm) | 15 |
| Weight (kg) | 0.113 |

Packaging

| | |
|---------------------------------------|----------------|
| Product EAN number | 5410288901152 |
| Packaging single length / height (cm) | 4.5 |
| Packaging single width (cm) | 3.0 |
| Packaging single depth (cm) | 26.0 |
| DUN14 (inner) | 15410288901159 |
| Units per outer package | 30 |
| Packaging outer length / height (cm) | 27.0 |
| Packaging outer width (cm) | 29.5 |
| Packaging outer depth (cm) | 17.5 |

Safety data

| | |
|----------------------------------|---------|
| Glow Wire Test (°C) | 650 |
| Optimal operating condition (°C) | 0 °C-40 |