

YourPro WaterProof 1500 IP65 6000LM 3CCT MultiPower

Item No: 0090272

SYLVANIA



YourPro WaterProof provides maximum performance and durability. Robust IK08 Waterproof IP65 Luminaire in 1500mm. Colour Switchable and Multi Power functions provides customers with flexibility to choose from 3000K, 4000K or 6500K and 20 / 40W power. High lumen package up to 6000lm and efficiency of 150lm/w. Ease of installation with metal clip, longer sliders and gland accessories included if required for through-wiring. 50,000 hour lifetime. 5 year warranty. Application areas include Car Parks, Underpass areas, Storage rooms, Workshops, Garages, Sheds.

Technical Assets

Photometrics

General data

Product name	YourPro WaterProof 1500 IP65 6000LM 3CCT MultiPower
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	6000
Luminaire efficacy (lm/W)	150
Light colour	Warm White or Neutral White or Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	120
Distribution type	Symmetric
Photobiological Risk Group	RG1

YourPro WaterProof 1500 IP65 6000LM 3CCT MultiPower

Item No: 0090272

SYLVANIA

Electrical data

Emergency type	
Total power consumption (W)	40
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	15
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Inrush Current (A)	24.6
Inrush Duration (µs)	206
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	12
Max. products per 16A C Breaker	19
Max. products per 16A B Breaker	13
Connectable conductor cross section - Max (mm ²)	2.5

Lifetime data

Lifespan L70 B50 | 50000

Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1500
Nominal Product Width (mm)	80
Nominal Product Height (mm)	68
Weight (kg)	1.5

Packaging

Product EAN number	5410288902722
Packaging single length / height (cm)	150.0
Packaging single width (cm)	7.9
Packaging single depth (cm)	6.8
DUN14 (inner)	15410288902729
Units per outer package	8
Packaging outer length / height (cm)	152.5
Packaging outer width (cm)	18.7
Packaging outer depth (cm)	31.6

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-20-40