

OPTIX SURFACE 1500 ASYMMETRIC 4000K

Item No: 2021734


Concord




OPTIX SURFACE 1500 ASYMMETRIC 4000K is a surface or wall mounted LED Linear luminaire with Asymmetric Aluminium Reflector, Asymmetric Light Distribution, Luminaire Dimensions: 1480x200x50mm, Sylvania White body colour, IP20, IK07, Constant Current, Low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 4250lm, 37W, 115lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, lifespan: 58,000 hours L90B10.

Technical Assets

Dimensions (mm)



Photometrics



OPTIX SURFACE 1500 ASYMMETRIC 4000K

Item No: 2021734

Concord

General data

Product name	OPTIX SURFACE 1500 ASYMMETRIC 4000K
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Built in presence detector	NONE
General application	Education
Operating temperature range (°C)	10°C...+25°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
E-number FI	4262045
Warranty	5 years

Optical data

Fixture luminous flux (lm)	4250
Luminaire efficacy (lm/W)	115
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Asymmetric
Photobiological Risk Group	RG0

Electrical data

Emergency type	
Total power consumption (W)	37
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	300
Inrush Current (A)	15
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	C, C(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	30
Max. products per 13A C Breaker	39
Max. products per 16A C Breaker	48
Max. products per 20A C Breaker	60
Max. products per 10A B Breaker	30
Max. products per 13A B Breaker	39
Max. products per 16A B Breaker	48
Max. products per 20A B Breaker	60
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	2.5

OPTIX SURFACE 1500 ASYMMETRIC 4000K

Item No: 2021734

Concord

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	58000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Other
Diffuser material	PC Polycarbonate
Reflector finish	Matt
Nominal Product Length (mm)	1480
Nominal Product Width (mm)	200
Nominal Product Height (mm)	50
Weight (kg)	5.6

Packaging

Product EAN number	5025768217342
Packaging single length / height (cm)	155.0
Packaging single width (cm)	9.0
Packaging single depth (cm)	21.0
DUN14 (inner)	05025768217342
Units per outer package	1
Packaging outer length / height (cm)	155.0
Packaging outer width (cm)	9.0
Packaging outer depth (cm)	21.0

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	10-25