


Solstice 100 1475lm 940 DIM WW

Item No: 2060859


Concord



The Solstice 100 1475lm 940 DIM WW is a high efficient phase dimmable downlight luminaire, Colour rendering index Ra>90, Colour temperature: 4000K Neutral White, Class II, Protection rating IP44/IP20, Cut out dimensions: 100mm

Technical Assets


Dimensions (mm)



Photometrics

0.5	0.77	50°	50°	3074
		50°	50°	918
1.0	1.54	50°	50°	918
		50°	50°	229
1.5	2.31	50°	50°	408
		50°	50°	102
2.0	3.08	50°	50°	230
		50°	50°	57
2.5	3.85	50°	50°	147
		50°	50°	37
3.0	4.62	50°	50°	102
		50°	50°	26

Distance [m] Cone diameter [m]
— C0 - C180 (Half beam angle: 75.2°)



Solstice 100 1475lm 940 DIM WW

Item No: 2060859

Concord

General data

Product name	Solstice 100 1475lm 940 DIM WW
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Built in presence detector	NONE
General application	Hospitality, Retail
Operating temperature range (°C)	5°C...+35°C
Virtual assistant compatibility	N/A
ETIM Class	EC001744
E-number FI	4170478
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1475
Luminaire efficacy (lm/W)	105
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	75
Distribution type	Symmetric
Glare control	< 27
Photobiological Risk Group	RG0

Electrical data

Emergency type	
Total power consumption (W)	14
Supply current (A)	1
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	0.2
Electrical protection	Class II
Control gear required	Yes
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Drive current (mA)	350
Inrush Current (A)	10
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	81
Max. products per 16A C Breaker	131
Max. products per 10A B Breaker	51
Max. products per 16A B Breaker	82
Connectable conductor cross section - Min (mm²)	0.5
Connectable conductor cross section - Max (mm²)	1.5

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B50	100000
Lifespan L90 B50	56000

Solstice 100 1475lm 940 DIM WW

Item No: 2060859

Concord

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP44/20
IK rating	IK03
Diffuser finish	Diffuse
Diffuser material	PC Polycarbonate
Reflector finish	High-gloss
Nominal Product Height (mm)	92
Nominal Product Diameter (mm)	112
Built-in diameter (mm)	100
Weight (kg)	0.43

Packaging

Product EAN number	5025768608591
Packaging single length / height (cm)	13.5
Packaging single width (cm)	13.5
Packaging single depth (cm)	16.5
DUN14 (inner)	05025768608591
Units per outer package	1
Packaging outer length / height (cm)	13.5
Packaging outer width (cm)	13.5
Packaging outer depth (cm)	16.5

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	5-35