

CONTINUUM PLUS 2.4 940 ST OPAL DI DALI EM W

Item No: 2064589

Concord



CONTINUUM PLUS 2.4 940 ST OPAL DI DALI EM W is a linear luminaire for suspended mounting with 3 meter pre-wiring and complete with end caps and suspension cables, direct/indirect light distribution (60/40 ratio), compact and minimalist design, ideal for offices, meeting rooms, corridors, education facilities, museums and libraries, white (RAL9016) finishing, extruded aluminium body, 2409x56x85mm dimensions, opal diffuser, 4000K (neutral white) colour temperature, total system power: 75W, total fixture output: 10200lm, luminaire efficacy: 136lm/W, colour rendering: Ra >90, LED Chromacity: 3 step MacAdam ellipse, lifespan: 89,000 hours L80B50, operating voltage: 220-240V / 50-60Hz, drive current: 1700mA, electronic driver, DALI dimmable, 3-hours LiFePO4 integrated DALI Self Test emergency, direct/indirect independently addressable, Class I electrical protection, IP20, IK03, suitable for internal environment only.

Technical Assets

Dimensions (mm)




Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam angle [°]	Beam angle [°]	Beam angle [°]	Illuminance [lx]
0.5	1.23	0.77	90°	90°	90°	8036
	1.31	0.82	90°	90°	90°	1110
1.0	2.45	1.54	90°	90°	90°	2206
	2.62	1.64	90°	90°	90°	219
1.5	3.68	2.31	90°	90°	90°	961
	3.92	2.44	90°	90°	90°	654
2.0	4.90	3.06	90°	90°	90°	562
	5.23	3.26	90°	90°	90°	413
2.5	6.13	3.89	90°	90°	90°	393
	6.54	4.14	90°	90°	90°	285
3.0	7.36	4.80	90°	90°	90°	246
	7.85	5.09	90°	90°	90°	181

Distance [m] Cone diameter [m] Beam diameter [m] Beam angle [°] Beam angle [°] Beam angle [°] Illuminance [lx]

— C0 - C180 (Half beam angle: 105.2°) — C90 - C270 (Half beam angle: 101.6°)



CONTINUUM PLUS 2.4 940 ST OPAL DI DALI EM W

Item No: 2064589

Concord

General data

Product name	CONTINUUM PLUS 2.4 940 ST OPAL DI DALI EM W
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Built in presence detector	NONE
Fixture rating	Enclosed
General application	Office, Education, Retail
Operating temperature range (°C)	1°C...+25°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	10200
Luminaire efficacy (lm/W)	136
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	255

Electrical data

Emergency mode	Maintained
Emergency type	
Emergency duration (h)	3
Total power consumption (W)	75
Supply current (A)	0.327
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Minimum dimming level (%)	1
Drive current (mA)	1700
Inrush Current (A)	31.5
Inrush Duration (µs)	215
Energy Efficiency Class (A->G) of contained light source	C, B (more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	15
Max. products per 13A C Breaker	20
Max. products per 16A C Breaker	25
Max. products per 20A C Breaker	32
Max. products per 10A B Breaker	9
Max. products per 13A B Breaker	12
Max. products per 16A B Breaker	15
Max. products per 20A B Breaker	19
Connectable conductor cross section - Min (mm ²)	0.75
Connectable conductor cross section - Max (mm ²)	1.5

CONTINUUM PLUS 2.4 940 ST OPAL DI DALI EM W

Item No: 2064589

Concord

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B50	89000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK03
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	Not Applicable
Nominal Product Length (mm)	2409
Nominal Product Width (mm)	56
Nominal Product Height (mm)	85
Weight (kg)	6.8

Packaging

Product EAN number	5025768645893
Packaging single length / height (cm)	251.0
Packaging single width (cm)	11.7
Packaging single depth (cm)	14.7
DUN14 (inner)	05025768645893
Units per outer package	1
Packaging outer length / height (cm)	251.0
Packaging outer width (cm)	11.7
Packaging outer depth (cm)	14.7

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	1-25