

CONTINUUM PLUS TR L-COR 940 UGR D DALI W

Item No: 2064614

Concord

General data

Product name	CONTINUUM PLUS TR L-COR 940 UGR D DALI W
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
Built in presence detector	NONE
Fixture rating	Enclosed
General application	Office, Education, Retail
Operating temperature range (°C)	1°C...+25°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1575
Luminaire efficacy (lm/W)	137
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

Electrical data

Emergency type	
Total power consumption (W)	11.5
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Minimum dimming level (%)	1
Drive current (mA)	250
Inrush Current (A)	7.5
Inrush Duration (µs)	220
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	70
Max. products per 13A C Breaker	90
Max. products per 16A C Breaker	110
Max. products per 20A C Breaker	138
Max. products per 10A B Breaker	42
Max. products per 13A B Breaker	54
Max. products per 16A B Breaker	66
Max. products per 20A B Breaker	83
Connectable conductor cross section - Min (mm ²)	0.75
Connectable conductor cross section - Max (mm ²)	1.5

CONTINUUM PLUS TR L-COR 940 UGR D DALI W

Item No: 2064614

Concord

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B50	89000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK03
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Reflector finish	Not Applicable
Nominal Product Length (mm)	342
Nominal Product Width (mm)	80
Nominal Product Height (mm)	85
Weight (kg)	1.6

Packaging

Product EAN number	5025768646142
Packaging single length / height (cm)	36.5
Packaging single width (cm)	38.2
Packaging single depth (cm)	11.0
DUN14 (inner)	05025768646142
Units per outer package	1
Packaging outer length / height (cm)	36.5
Packaging outer width (cm)	38.2
Packaging outer depth (cm)	11.0

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	1-25