

# CONTINUUM PLUS 1.2 940 CO OPAL DI SSA03 EM B

Item No: 2064661


Concord



CONTINUUM PLUS 1.2 940 CO OPAL DI SSA03 EM B is a linear luminaire with trimless body for suspended mounting, various mounting accessories, direct/indirect light distribution (60/40 ratio), compact and minimalist design, ideal for offices, meeting rooms, corridors, education facilities, museums and libraries, black (RAL9005) finishing, extruded aluminium body, 1290x56x93mm dimensions, opal diffuser, 4000K (neutral white) colour temperature, total system power: 40W, total fixture output: 5100lm, luminaire efficacy: 128lm/W, colour rendering: Ra >90, LED Chromacity: 3 step MacAdam ellipse, lifespan: 89,000 hours L80B50, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, Sylsmart® Connected enabled, 3-hours LiFePO4 integrated DALI Self Test emergency, direct/indirect independently addressable, Class I electrical protection, IP20, IK03, suitable for internal environment only. The product is delivered without diffuser, end cap, suspension or power supply kit, the accessories eg rolled diffuser (2064605) to be ordered separately.

## Technical Assets


### Dimensions (mm)



### Photometrics

| Distance [m] | Cone diameter [m] | Beam diameter [m] | Illuminance [lx] |
|--------------|-------------------|-------------------|------------------|
| 0.5          | 1.23              | 0.51              | 4413             |
|              | 1.31              | 0.52              | 389              |
| 1.0          | 2.45              | 1.03              | 1103             |
|              | 2.62              | 1.06              | 131              |
| 1.5          | 3.65              | 1.54              | 490              |
|              | 3.92              | 1.61              | 85               |
| 2.0          | 4.90              | 2.05              | 275              |
|              | 5.23              | 2.14              | 51               |
| 2.5          | 6.13              | 2.56              | 177              |
|              | 6.54              | 2.67              | 32               |
| 3.0          | 7.35              | 3.00              | 133              |
|              | 7.85              | 3.14              | 14               |

Distance [m]    Cone diameter [m]    Beam diameter [m]    Illuminance [lx]  
 — C0 - C180 (Half beam angle: 105.2°)  
 — C90 - C270 (Half beam angle: 101.8°)



# CONTINUUM PLUS 1.2 940 CO OPAL DI SSA03 EM B

Item No: 2064661

**Concord**

## General data

|                                  |  |
|----------------------------------|--|
| Product name                     | CONTINUUM PLUS 1.2<br>940 CO OPAL DI SSA03<br>EM B |
| Technology                       | LED  |
| Cap/Base                         | N/A  |
| Housing                          | Aluminium  |
| Mount                            | Suspended  |
| Built in presence detector       | PIR  |
| Fixture rating                   | Enclosed   |
| General application              | Office, Education, Retail                          |
| Operating temperature range (°C) | 1°C...+25°C  |
| Virtual assistant compatibility  | N/A  |
| ETIM Class                       | EC002892   |
| Warranty                         | 5 years  |

## Optical data

|                                   |               |
|-----------------------------------|---------------|
| Fixture luminous flux (lm)        | 5100          |
| Luminaire efficacy (lm/W)         | 128           |
| Correlated colour temperature (k) | 4000          |
| Light colour                      | Neutral White |
| CRI (Ra)                          | 90            |
| Colour Variation Initial (SDCM)   | SDCM3         |
| Distribution type                 | Symmetric     |
| Glare control                     | < 25          |
| Photobiological Risk Group        | RG1           |
| Luminous flux (emergency) (lm)    | 255           |

## Electrical data

|  |                                 |
|--|---------------------------------|
| Emergency mode   | Maintained                      |
| Emergency type   |                                 |
| Emergency duration (h)   | 3                               |
| Total power consumption (W)                                      | 40                              |
| Supply current (A)   | 0.186                           |
| Primary Supply/Product voltage - min (V)                         | 220.0                           |
| Primary Supply/Product voltage - max (V)                         | 240.0                           |
| Lamp power factor  | 0.97                            |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 10                              |
| Electrical protection  | Class I                         |
| Control gear required  | No                              |
| Control gear type  | LED driver constant current     |
| Dimmable   | Yes                             |
| Dimming method   | SylSmart Connected (SSA)        |
| Minimum dimming level (%)  | 1                               |
| Drive current (mA)   | 500                             |
| Inrush Current (A)   | 29                              |
| Inrush Duration (µs)   | 180                             |
| Energy Efficiency Class (A->G) of contained light source         | C, B (more than 1 Light Source) |
| Nominal Frequency (Hz)   | 50/60Hz                         |
| LED Flickering Rate  | Ultra low (5% or less)          |
| Max. products per 10A C Breaker                                  | 21                              |
| Max. products per 13A C Breaker                                  | 28                              |
| Max. products per 16A C Breaker                                  | 36                              |
| Max. products per 20A C Breaker                                  | 45                              |
| Max. products per 10A B Breaker                                  | 13                              |
| Max. products per 13A B Breaker                                  | 17                              |
| Max. products per 16A B Breaker                                  | 22                              |
| Max. products per 20A B Breaker                                  | 27                              |
| Connectable conductor cross section - Min (mm²)                  | 0.75                            |

# CONTINUUM PLUS 1.2 940 CO OPAL DI SSA03 EM B

Item No: 2064661

## Concord

|  |                      |                                       |                |
|--|----------------------|---------------------------------------|----------------|
| Connectable conductor cross section - Max (mm <sup>2</sup> ) | 1.5                  | <b>Packaging</b>                      |                |
| <b>Lifetime data</b>   |                      | Product EAN number                    | 5025768646616  |
| Lifespan L70 B50   | 100000               | Packaging single length / height (cm) | 139.0          |
| Lifespan L80 B50   | 89000                | Packaging single width (cm)           | 11.7           |
| <b>Physical data</b>   |                      | Packaging single depth (cm)           | 14.7           |
| Housing colour   | RAL 9005 - Jet black | DUN14 (inner)                         | 05025768646616 |
| IP rating  | IP20                 | Units per outer package               | 1              |
| IK rating  | IK03                 | Packaging outer length / height (cm)  | 139.0          |
| Diffuser finish  | Opal                 | Packaging outer width (cm)            | 11.7           |
| Diffuser material  | PC Polycarbonate     | Packaging outer depth (cm)            | 14.7           |
| Reflector finish   | Not Applicable       | <b>Safety data</b>                    |                |
| Nominal Product Length (mm)                                  | 1290                 | Glow Wire Test (°C)                   | 650            |
| Nominal Product Width (mm)                                   | 56                   | Optimal operating condition (°C)      | 1-25           |
| Nominal Product Height (mm)                                  | 93                   |                                       |                |
| Weight (kg)  | 3.6                  |                                       |                |