

# Pixo Line Driver Multipower 600 Black

Item No: 0007866

**SYLVANIA**


**PRO**<sup>TM</sup>



Pixo Line is a linear track system, adds flexibility to any space due the variety of product optionsOffers an easy installation with two separate modulesPush-in/push-out mechanism with GR6d-15 connectorCompatible with Zhaga Book 14Constant current 350mA -1050mA LED in-track driver with GR6d-15 connector for LED light modules, polycarbonate bodyClip holder and fixing screw included in the driver box, black finishing colour, max. system power: 56W, operating voltage: 220-240V / 50-60HzDriver module should be combined with suitable LED module. Multipower driver module with 8 power settings meet all installation needs with one single product selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA)Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrackElectrical protection: Class I. Degree of protection: IP20, suitable for indoor environment onlyLight modules should be combined with suitable in-track driversNominal product dimensions: L.672mmx32mmx31mm. This driver can be combined with Pixo Line 1500, and Pixo Line 900 (max.29W-600mA)

## Technical Assets

### Dimensions (mm)



### Photometrics

# Pixo Line Driver Multipower 600 Black

Item No: 0007866

**SYLVANIA**

## General data

Product name	Pixo Line Driver Multipower 600 Black
Technology	Driver
Mount	Track mounting
General application	Hospitality, Museums & Galleries, Office, Retail
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC002710
E-number FI	4279417
Warranty	5 years

## Optical data

Light colour	N/A
Photobiological Risk Group	Not applicable

## Electrical data

Total power consumption (W)	56
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	10
Electrical protection	Class I
No. Of switching cycles before premature failures	>100000
Dimmable	No
Dimming method	N/A
Min. drive current (mA)	350
Max. drive current (mA)	1050
Drive current - Range (mA)	350mA / 1050mA
Inrush Current (A)	42
Inrush Duration ( $\mu$ s)	168
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	15
Max. products per 16A C Breaker	24
Max. products per 10A B Breaker	9
Max. products per 16A B Breaker	14
Mains surge immunity (differential mode -> L-N) (kV)	1

## Physical data

Housing colour	Black
IP rating	IP20
IK rating	IK03
Nominal Product Length (mm)	672
Nominal Product Width (mm)	31
Nominal Product Height (mm)	31.5
Weight (kg)	0.36

# Pixo Line Driver Multipower 600 Black

Item No: 0007866

**SYLVANIA**

## Packaging

Product EAN number	5410288078663
Packaging single length / height (cm)	68.0
Packaging single width (cm)	5.0
Packaging single depth (cm)	3.7
DUN14 (inner)	15410288078660
Units per outer package	20
Packaging outer length / height (cm)	70.0
Packaging outer width (cm)	27.0
Packaging outer depth (cm)	17.0

## Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40