

# ToLED<sub>o</sub> SUPERIA T5 AC 5FT 4000LM 840

Item No: 0028040

**SYLVANIA**



50,000 hours average rated lifetime (L70 F50) Last 2.5 times longer than 49W 1449mm fluorescent tri-phosphor T5 lamp  
High switching cycles - 200,000X High lumen efficacy - 154lm/W  
Omni-directional light distribution and wide beam angle  
Minimum and maximum operating temperature: -20°C to 50°C  
Glass construction and polycarbonate end-caps  
Only suitable for direct mains (AC 220-240V) operation  
Ideal for factories, parking lots, supermarkets, department stores, schools and offices  
Not suitable for operation with electronic/ECG or magnetic/CCG ballasts

## Technical Assets

### Photometrics

#### General data

Product name	ToLED <sub>o</sub> SUPERIA T5 AC 5FT 4000LM 840
Technology	LED
Watt (Rated) (W)	26
Cap/Base	G5
General application	Office, Hospitality, Logistics & Industry, Retail, Residential & Consumer, Museums & Galleries, Education
ETIM Class	EC001959
E-number FI	4740765
Warranty	5 years

#### Optical data

Luminous flux (Rated) (lm)	4000
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Lumen maintenance at end of nominal life (%)	70

#### Electrical data

Power consumption (W)	26
Wattage (W)	26
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<2
Lamp power factor	0.9
No. Of switching cycles before premature failures	>200000
Dimmable	No

#### Lifetime data

Average life (Nominal) (h)	50000
Average life (Rated) (h)	50000

#### Physical data

Weight (kg)	0.174
-------------	-------

# ToLEDo SUPERIA T5 AC 5FT 4000LM 840

Item No: 0028040



## Packaging

Product EAN number	5410288280400
Packaging single length / height (cm)	146.2
Packaging single width (cm)	1.8
Packaging single depth (cm)	1.8
DUN14 (inner)	15410288280407
Units per outer package	10
Packaging outer length / height (cm)	152.5
Packaging outer width (cm)	15.6
Packaging outer depth (cm)	8.0

## Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture