

ToLEDo BALL V6 806LM 865 E27 SL

Item No: 0028438

SYLVANIA



- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent ball lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating

Technical Assets

Photometrics

General data

Product name	ToLEDo BALL V6 806LM 865 E27 SL
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740810
Warranty	3 years

Optical data

Useful luminous flux (Φ_{use})	806
Luminous flux (Rated) (lm)	806
Correlated colour temperature (k)	6500
Light colour	Daylight
CRI (Ra)	80
Beam Angle (°)	150
Lumen maintenance at end of nominal life (%)	70

ToLEDo BALL V6 806LM 865 E27 SL

Item No: 0028438

SYLVANIA

Electrical data

Power consumption (W)	8
Wattage (W)	8
Equivalent watt (W)	60
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Lamp power factor	0.5
No. Of switching cycles before premature failures	>50000
Inrush Current (A)	2.7
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	131
Max. products per 16A C Breaker	211
Max. products per 20A C Breaker	364

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	90
Nominal Product Diameter (mm)	45
Weight (kg)	0.045

Packaging

Product EAN number	5410288284385
Packaging single length / height (cm)	4.5
Packaging single width (cm)	4.5
Packaging single depth (cm)	8.9
DUN14 (inner)	15410288284382
Units per outer package	6
Packaging outer length / height (cm)	14.3
Packaging outer width (cm)	9.7
Packaging outer depth (cm)	8.5

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures