

TOLEDO RT GLS V3 ST DIM 1055LM 840 E27

Item No: 0028605

SYLVANIA



- Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- A++ energy rating
- Suitable replacement for incandescent and halogen lamps
- Gives same sparkling light effect as incandescent lamp
- Dimensionally identical to incandescent lamps - fits all fixtures
- Environment friendly - no mercury and lower CO2 emissions

Technical Assets

Photometrics

General data

| | |
|---|--|
| Product name | TOLEDO RT GLS V3 ST DIM 1055LM 840 E27 |
| Technology | LED |
| Watt (Rated) (W) | 9 |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Hospitality, Residential & Consumer |
| Performance ambient temperature Tq (°C) | 25 |
| ETIM Class | EC001959 |
| E-number FI | 4740883 |
| Warranty | 3 years |

Optical data

| | |
|--|------------|
| Useful luminous flux (Φ_{use}) | 1055 |
| Luminous flux (Rated) (lm) | 1055 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Cool White |
| CRI (Ra) | 80 |
| Lumen maintenance at end of nominal life (%) | 70 |

TOLEDO RT GLS V3 ST DIM 1055LM 840 E27

Item No: 0028605

SYLVANIA

Electrical data

| | |
|---|---------|
| Power consumption (W) | 8 |
| Wattage (W) | 9 |
| Starting time (max) (s) | 0.5 |
| Warm-up time to 60% of full light (max) (s) | 1 |
| Lamp power factor | 0.75 |
| Control gear required | No |
| No. Of switching cycles before premature failures | >50000 |
| Dimmable | Yes |
| Inrush Current (A) | 1.5 |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 43 |
| Max. products per 16A C Breaker | 70 |
| Max. products per 20A C Breaker | 87 |

Lifetime data

| | |
|----------------------------|-------|
| Average life (Nominal) (h) | 15000 |
| Average life (Rated) (h) | 15000 |

Physical data

| | |
|-------------------------------|-------|
| Nominal Product Length (mm) | 104 |
| Nominal Product Diameter (mm) | 60 |
| Weight (kg) | 0.065 |

Packaging

| | |
|---------------------------------------|----------------|
| Product EAN number | 5410288286051 |
| Packaging single length / height (cm) | 6.6 |
| Packaging single width (cm) | 6.6 |
| Packaging single depth (cm) | 12.0 |
| DUN14 (inner) | 15410288286058 |
| Units per outer package | 6 |
| Packaging outer length / height (cm) | 20.6 |
| Packaging outer width (cm) | 13.9 |
| Packaging outer depth (cm) | 13.0 |

Safety data

| | |
|-------------------------------------|--|
| Breakage cleaning instructions | Not applicable |
| Special purpose lamp | No |
| Dry applications use only | Yes |
| Suitable for household illumination | Yes |
| Safety message | Not Suitable for totally enclosed fixtures |