

# ToLEDo SUPERIA T8 CCG L1200 2760LM 830 75K PET SL

Item No: 0030245


**SYLVANIA**



A range of high performance ToLEDo Superia T8 LED tubes with reminiscent look of fluorescent tubes High performance glass construction design High lumen output, with an impressive lumen efficacy of 164 lm/W Omnidirectional light distribution and wide beam angle Average rated life of 75,000 hours Lamp length - 1200mm High power factor 200,000 switching cycle 5 years warranty for complete peace of mind Compatible with electromagnetic gear / CCG and also suitable for direct mains operation (220-240V) No bending or discoloration over time Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots, waterproof luminaires and maintenance free applications

## Technical Assets

### Dimensions (mm)



### Photometrics

# ToLED<sub>o</sub> SUPERIA T8 CCG L1200 2760LM 830 75K PET SL

Item No: 0030245

**SYLVANIA**

## General data

Product name	ToLED <sub>o</sub> SUPERIA T8 CCG L1200 2760LM 830 75K PET SL
Technology	LED
Lamp shape	Tube, double-ended
Cap/Base	G13
Lamp finish	Frosted/Coated
General application	Hospitality, Logistics & Industry, Residential & Consumer
Operating temperature range (°C)	-20°C...+55°C
Virtual assistant compatibility	N/A
ETIM Class	EC001959
E-number FI	4941350
Warranty	5 years

## Optical data

Useful luminous flux (Φ <sub>use</sub> )	2760
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	170
Photobiological Risk Group	RG0

## Electrical data

Power consumption (W)	16.8
Wattage (W)	16.8
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Control gear required	No
Dimmable	No
Inrush Current (A)	10.4
Inrush Duration (µs)	50
Lamp Energy Label (class)	C

## Lifetime data

Lifespan L70 B50	75000
------------------	-------

## Physical data

IP rating	IP20
Nominal Product Length (mm)	1198
Nominal Product Diameter (mm)	28
Weight (kg)	0.19

## Packaging

Product EAN number	5410288302454
Packaging single length / height (cm)	125.1
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (inner)	15410288302451
Units per outer package	10
Packaging outer length / height (cm)	130.0
Packaging outer width (cm)	23.1
Packaging outer depth (cm)	11.0

## Safety data

Optimal operating condition (°C)	-20-55
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture