

LIFESAFE PRO SURF RDDDL HO RARC EM3NMDABK

Item No: 0038813

SYLVANIA

LiFeSafe



UK
CA




LiFeSafe PRO SURF RDDDLHO RA C EM3 NM DA BK is a black high output DALI addressable round surface mount standalone luminaire. Non-maintained self-test 3Hr emergency duration with LiFePO4 rechargeable batteries. Interchangeable lens for open area or corridor beam. 3.5W - 450lm , 20mm conduit entry points, IK06, IP20, Class II construction 6-year warranty.

Technical Assets

Dimensions (mm)

Surface Mount



Photometrics

LIFESAFE PRO SURF RDDDL HO RARC EM3NMDABK

Item No: 0038813



General data

Product name	LIFESAFE PRO SURF RDDDL HO RARC EM3NMDABK
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
Operating temperature range (°C)	0°C...+45°C
ETIM Class	EC001957
Warranty	6 years

Optical data

Fixture luminous flux (lm)	450
Luminaire efficacy (lm/W)	75
Correlated colour temperature (k)	5000
CRI (Ra)	70
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70
Luminous flux (emergency) (lm)	450

Electrical data

Emergency mode	Non-Maintained
Emergency type	
Emergency duration (h)	3
Supply current (A)	0.055
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.35
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	84.2
Electrical protection	Class II
Control gear required	Yes
Control gear type	LED driver constant current
Drive current (mA)	515
Inrush Current (A)	30
Inrush Duration (µs)	220
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	209
Max. products per 13A C Breaker	271
Max. products per 16A C Breaker	344
Max. products per 20A C Breaker	418
Max. products per 10A B Breaker	313
Max. products per 13A B Breaker	271
Max. products per 16A B Breaker	344
Max. products per 20A B Breaker	418
Connectable conductor cross section - Min (mm ²)	0.5
Connectable conductor cross section - Max (mm ²)	0.75

Lifetime data

Lifespan L70 B10	68000
Lifespan L90 B10	20000

LIFESAFE PRO SURF RDDDL HO RARC EM3NMDABK

Item No: 0038813

SYLVANIA

Physical data

Housing colour	Black
IP rating	IP20
IK rating	IK06
Diffuser finish	Prismatic
Diffuser material	PC Polycarbonate
Nominal Product Height (mm)	62
Nominal Product Diameter (mm)	140
Weight (kg)	0.49

Packaging

Product EAN number	5410288388137
Packaging single length / height (cm)	26.0
Packaging single width (cm)	19.0
Packaging single depth (cm)	9.0
DUN14 (inner)	05410288388137
Units per outer package	1
Packaging outer length / height (cm)	26.0
Packaging outer width (cm)	19.0
Packaging outer depth (cm)	9.0

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	0 °C-45
Dry applications use only	Yes