

Sylbay Gen II EM Kit Standard

Item No: 0040027




Sylbay Gen II EM Kit Standard provides a simple conversion of High Bay fitting with a high performance self-contained LED emergency luminaire KIT suitable for open areas, delivering 3 hours rated emergency output. Self testing with DALI monitoring capability. Supplied with all mounting accessories

Technical Assets

Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	1.45	0.07	88.4°	299
1.0	2.90	0.14	88.4°	75
1.5	4.35	0.21	88.4°	33
2.0	5.80	0.28	88.4°	19
2.5	7.25	0.35	88.4°	12
3.0	8.70	0.42	88.4°	8

Distance [m] Cone diameter [m] Beam diameter [m] Beam angle [°] Illuminance [lx]
 C0 - C180 (Half beam angle: 110.8°)



Sylbay Gen II EM Kit Standard

Item No: 0040027

SYLVANIA

General data

Product name	Sylbay Gen II EM Kit Standard
Technology	Emergency Pack
General application	Logistics & Industry
ETIM Class	EC002472
Warranty	3 years

Optical data

Fixture luminous flux (lm)	200
CRI (Ra)	75
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	200

Electrical data

Emergency duration (h)	3
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.44
Electrical protection	Class II

Physical data

Housing colour	White
IP rating	IP65
IK rating	IK03
Weight (kg)	1.1

Packaging

Product EAN number	5410288400273
Packaging single length / height (cm)	32.5
Packaging single width (cm)	32.5
Packaging single depth (cm)	12.5
DUN14 (inner)	05410288400273
Units per outer package	1
Packaging outer length / height (cm)	32.5
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	12.5