

ISOLINE 3380MM 4K MD UGR E3 8C

Item No: 0042544




PROTM



Isoline LED linear luminaire with 3hr integrated emergency function for industrial and commercial applications. 3380 mm length with wide optics provide homogeneous light distribution for open areas. Aluminium housing, RAL 9016. Max + 35 °C operating temperature range, 4000 K, CRI 80, UGR <20, 3 SDCM. 117 W power consumption, 17600 lm luminous flux, 150 lm/W efficacy, 3380 mm x 62 mm x 59 mm (L x W x H) dimensions, IP20, IK03, 220-240 V 50/60 Hz, Class I. Lifespan L70:B50 60,000 hours.


Technical Assets

Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	0.84	0.84	32.3°	240
			32.3°	768
			28.3°	651
1.0	1.27	1.00	32.3°	160
			32.3°	512
			28.3°	225
1.5	1.91	1.62	32.3°	107
			32.3°	358
			28.3°	161
2.0	2.55	2.15	32.3°	75
			32.3°	240
			28.3°	113
2.5	3.19	2.69	32.3°	60
			32.3°	192
			28.3°	88
3.0	3.82	3.23	32.3°	50
			32.3°	154
			28.3°	71



ISOLINE 3380MM 4K MD UGR E3 8C

Item No: 0042544

SYLVANIA

General data

Product name	ISOLINE 3380MM 4K MD UGR E3 8C
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	0°C...+30°C
ETIM Class	EC000986
Warranty	5 years

Optical data

Fixture luminous flux (lm)	17600
Luminaire efficacy (lm/W)	150
Correlated colour temperature (k)	4000
Colour Code	840
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	60
Glare control	< 20
Photobiological Risk Group	RG1

Electrical data

Emergency type	
Emergency duration (h)	3
Total power consumption (W)	117
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	250
Inrush Current (A)	25
Inrush Duration (µs)	250
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	13
Max. products per 13A C Breaker	17
Max. products per 16A C Breaker	22
Max. products per 20A C Breaker	29
Max. products per 10A B Breaker	8
Max. products per 13A B Breaker	10
Max. products per 16A B Breaker	13
Max. products per 20A B Breaker	17
Connectable conductor cross section - Min (mm ²)	0.5
Connectable conductor cross section - Max (mm ²)	4

ISOLINE 3380MM 4K MD UGR E3 8C

Item No: 0042544

SYLVANIA

Lifetime data

Lifespan L70 B50	60000
Lifespan L80 B10	60000
Lifespan L90 B10	31500

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK03
IK rating of sensor	IK03
Diffuser finish	Transparent
Diffuser material	PMMA Acrylic
Nominal Product Length (mm)	3380
Nominal Product Width (mm)	62
Nominal Product Height (mm)	59
Weight (kg)	6.0

Packaging

Product EAN number	5410288425443
Packaging single length / height (cm)	353.0
Packaging single width (cm)	6.5
Packaging single depth (cm)	5.8
DUN14 (inner)	05410288425443
Units per outer package	1
Packaging outer length / height (cm)	354.0
Packaging outer width (cm)	7.0
Packaging outer depth (cm)	6.3

Safety data

Glow Wire Test (°C)	650
---------------------	-----