



OptiClip 600 3000K C8 HO WH CC WHITE

Item No: 0043004

SYLVANIA


PROTM



OPTICLIP 600 3000K C8 HO WH CC WHITE is a high efficacy low glare luminaire with replaceable light engines for office and education applications. Ceiling recessed LED luminaire with white colour plastic optic, direct light distribution, luminaire dimensions: 595x595x20mm, Sylvania White body colour (RAL9016), IP40 (from the front), IK07, Constant Current driver, low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 3925lm luminous flux, 33W power consumption, 119lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<17, Luminance at 65° < 2000 cd/m2, lifespan: 62,000 hours L80B20, photobiological safety risk group 1. Electrical protection Class II. Glow wire test 850°C.

Technical Assets

Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [ft]	Beam diameter [in]	Illuminance [lx]
0.5	0.83 0.81	0.07	0.23'	2.91"	940
1.0	1.67 1.61	0.07	0.23'	2.91"	238
1.5	2.50 2.42	0.07	0.23'	2.91"	104
2.0	3.33 3.23	0.07	0.23'	2.91"	59
2.5	4.17 4.03	0.07	0.23'	2.91"	37
3.0	5.00 4.84	0.07	0.23'	2.91"	26

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 77.9°)
 — C90 - C270 (Half beam angle: 79.0°)

