


START Panel Flat UGR19 600x600 4000Lm 840

Item No: 0047229


SYLVANIA



Edge lit LED flat panel with low glare (UGR<19). Low Flicker, 40 W, Neutral White, 4000 K, 4000 lumens, 100 lm/W, Average lifespan: 120.000Hrs, prismatic diffuser, aluminium frame, steel body, electronic non dimmable driver. (HxWxD) 9.5 x 595 x 595 mm

Technical Assets

Dimensions (mm)




Photometrics

0.5	0.52 0.51	E171 E150 E100	7370 1551 1552
1.0	1.03 1.03	E171 E150 E100	1980 396 415
1.5	2.75 2.74	E171 E150 E100	875 175 185
2.0	3.67 3.65	E171 E150 E100	490 98 104
2.5	4.58 4.57	E171 E150 E100	315 63 66
3.0	5.50 5.48	E171 E150 E100	219 44 48

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 84.9°)
— C90 - C270 (Half beam angle: 85.0°)



START Panel Flat UGR19 600x600 4000Lm 840

Item No: 0047229

SYLVANIA

General data

Product name	START Panel Flat UGR19 600x600 4000Lm 840
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting, Ceiling surface mounting, Suspended
Environment	Interior
General application	Education, Office
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4276950
Warranty	5 years

Optical data

Fixture luminous flux (lm)	4,050
Luminaire efficacy (lm/W)	101
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	90
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	40
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	15.0
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	980
Inrush Current (A)	10
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	55
Max. products per 13A C Breaker	70
Max. products per 16A C Breaker	85
Max. products per 20A C Breaker	110

Lifetime data

Lifespan L70 B50	120000
------------------	--------

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP40/20
IK rating	IK03
Diffuser finish	Prismatic
Nominal Product Length (mm)	595
Nominal Product Width (mm)	595
Nominal Product Height (mm)	9.5
Weight (kg)	2.653
Recessed Depth (mm)	38

START Panel Flat UGR19 600x600 4000Lm 840

Item No: 0047229

SYLVANIA

Packaging

Product EAN number	5410288472294
Packaging single length / height (cm)	63.0
Packaging single width (cm)	4.4
Packaging single depth (cm)	67.5
DUN14 (inner)	15410288472291
Units per outer package	2
Packaging outer length / height (cm)	65.0
Packaging outer width (cm)	10.8
Packaging outer depth (cm)	69.5

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-20-40