


START eco Panel 600x600 3200Lm 865

Item No: 0047671


SYLVANIA



Back lit LED panel, Low Flicker, 36 W, Cool White, 6500 K, 3200 lumens, 89 lm/W, Average lifespan: 100.000Hrs, electronic non dimmable driver. (HxWxD) 34 x 595 x 595 mm.


Technical Assets

Dimensions (mm)



Photometrics

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Beam area [m²]	Illuminance [lx]
0.5	1.52	50°	1.52	2.25	1440
1.0	3.03	50°	3.03	9.18	360
1.5	4.55	50°	4.55	20.5	158
2.0	6.07	50°	6.07	36.8	87
2.5	7.58	50°	7.58	57.2	56
3.0	9.10	50°	9.10	82.1	39



START eco Panel 600x600 3200Lm 865

Item No: 0047671

SYLVANIA

General data

Product name	START eco Panel 600x600 3200Lm 865
Technology	LED
Housing	Aluminium, Steel
Mount	Ceiling recessed mounting
Environment	Interior
General application	Education, Office
Operating temperature range (°C)	-10°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	3 years

Optical data

Fixture luminous flux (lm)	3200
Luminaire efficacy (lm/W)	89
Correlated colour temperature (k)	6500
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	112
Distribution type	Symmetric
Glare control	< 22
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	36
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	15.0
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	750
Inrush Current (A)	14.6
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	45
Max. products per 13A C Breaker	60
Max. products per 16A C Breaker	74
Max. products per 20A C Breaker	93

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	71000

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP40/20
IK rating	IK02
Diffuser material	Other
Nominal Product Length (mm)	595
Nominal Product Width (mm)	595
Nominal Product Height (mm)	34
Weight (kg)	1.654

START eco Panel 600x600 3200Lm 865

Item No: 0047671



Packaging

Product EAN number	5410288476711
Packaging single length / height (cm)	60.7
Packaging single width (cm)	3.7
Packaging single depth (cm)	64.4
DUN14 (inner)	15410288476718
Units per outer package	1
Packaging outer length / height (cm)	60.7
Packaging outer width (cm)	3.7
Packaging outer depth (cm)	64.4

Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	-10-45