



SylWork Flood 3000LM 840 IP65

Item No: 0090003

SYLVANIA


YourHome™



- Slim LED portable work light • Lightweight, slim, stylish robust, high-quality plastic body • Stable, flexible positioning with stand or Tripod • Housing material: PC housing, glass lens and metal bracket • Option to use 2 work lights in the same time installed on the same Tripod • Mains operated version • Space-saving design – Tripod version can be folded up and stowed away • 4000K Cool White light • Total system efficacy up to 100lm/W • CRI >80 • Operating temperature range: -20 to +40°C • Lifetime: 30.000 hrs (L70/B50) • 3 year warranty

Technical Assets

Dimensions (mm)



Photometrics

SylWork Flood 3000LM 840 IP65

Item No: 0090003

SYLVANIA

General data

Product name	SylWork Flood 3000LM 840 IP65
Technology	LED
Cap/Base	N/A
Housing	Metal/plastic
General application	Residential & Consumer
ETIM Class	EC000346
E-number FI	4357145
Warranty	3 years

Optical data

Fixture luminous flux (lm)	3000
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	30
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Electrical protection	Class I
Dimmable	Yes
Dimming method	Onboard pot
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50Hz
Connectable conductor cross section - Max (mm ²)	1.0

Lifetime data

Lifespan L70 B50	30000
Lifespan L90 B10	10000

Physical data

IP rating	IP65
IK rating	IK07
Nominal Product Length (mm)	230
Nominal Product Width (mm)	163
Nominal Product Height (mm)	43
Weight (kg)	0.95

Packaging

Product EAN number	5410288900032
Packaging single length / height (cm)	18.8
Packaging single width (cm)	6.2
Packaging single depth (cm)	25.5
DUN14 (inner)	15410288900039
Units per outer package	8
Packaging outer length / height (cm)	39.0
Packaging outer width (cm)	26.5
Packaging outer depth (cm)	27.5