

CONTINUUM PLUS 1.2 940 ST UGR DI SSA03 W

Item No: 2064636


Concord



CONTINUUM PLUS 1.2 940 ST UGR DI SSA03 W is a linear luminaire for suspended mounting with 3 meter pre-wiring and complete with end caps and suspension cables, direct/indirect light distribution (60/40 ratio), compact and minimalist design, ideal for offices, meeting rooms, corridors, education facilities, museums and libraries, white (RAL9016) finishing, extruded aluminium body, 1294x56x93mm dimensions, prismatic diffuser combined with lenses, 4000K (neutral white) colour temperature, total system power: 37W, total fixture output: 5350lm, luminaire efficacy: 145lm/W, colour rendering: Ra >90, LED Chromacity: 3 step MacAdam ellipse, lifespan: 89,000 hours L80B50, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, SylSmart® Connected enabled, direct/indirect independently addressable, Class I electrical protection, IP20, IK03, suitable for internal environment only.

Technical Assets

Dimensions (mm)



Photometrics

| Distance [m] | Cone diameter [m] | Beam diameter [m] | Illuminance [lx] |
|--------------|-------------------|-------------------|--|
| 0.5 | 0.73 | 0.71 | 9000 |
| | | | 5107 E100 35.1° E100 35.3° E100 35.3° |
| 1.0 | 1.46 | 1.42 | 2216 |
| | | | 5107 E100 35.1° E100 35.3° E100 35.3° |
| 1.5 | 2.19 | 2.12 | 1074 |
| | | | 5107 E100 35.1° E100 35.3° E100 35.3° |
| 2.0 | 2.92 | 2.83 | 604 |
| | | | 5107 E100 35.1° E100 35.3° E100 35.3° |
| 2.5 | 3.65 | 3.54 | 387 |
| | | | 5107 E100 35.1° E100 35.3° E100 35.3° |
| 3.0 | 4.38 | 4.25 | 290 |
| | | | 5107 E100 35.1° E100 35.3° E100 35.3° |

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 72.6°)
 — C90 - C270 (Half beam angle: 72.2°)



CONTINUUM PLUS 1.2 940 ST UGR DI SSA03 W

Item No: 2064636

Concord

General data

| | |
|----------------------------------|--|
| Product name | CONTINUUM PLUS 1.2 940 ST UGR DI SSA03 W |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Suspended |
| Built in presence detector | PIR |
| Fixture rating | Enclosed |
| General application | Office, Education, Retail |
| Operating temperature range (°C) | 1°C...+25°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC002892 |
| Warranty | 5 years |

Optical data

| | |
|-----------------------------------|---------------|
| Fixture luminous flux (lm) | 5350 |
| Luminaire efficacy (lm/W) | 145 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Neutral White |
| CRI (Ra) | 90 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Distribution type | Symmetric |
| Glare control | < 19 |
| Photobiological Risk Group | RG1 |

Electrical data

| | |
|--|---------------------------------|
| Emergency type | |
| Total power consumption (W) | 37 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.97 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 10 |
| Electrical protection | Class I |
| Control gear required | No |
| Control gear type | LED driver constant current |
| Dimmable | Yes |
| Dimming method | SylSmart Connected (SSA) |
| Minimum dimming level (%) | 1 |
| Drive current (mA) | 500 |
| Inrush Current (A) | 29 |
| Inrush Duration (µs) | 180 |
| Energy Efficiency Class (A->G) of contained light source | C, B (more than 1 Light Source) |
| Nominal Frequency (Hz) | 50/60Hz |
| LED Flickering Rate | Ultra low (5% or less) |
| Max. products per 10A C Breaker | 21 |
| Max. products per 13A C Breaker | 28 |
| Max. products per 16A C Breaker | 36 |
| Max. products per 20A C Breaker | 45 |
| Max. products per 10A B Breaker | 13 |
| Max. products per 13A B Breaker | 17 |
| Max. products per 16A B Breaker | 22 |
| Max. products per 20A B Breaker | 27 |
| Connectable conductor cross section - Min (mm ²) | 0.75 |
| Connectable conductor cross section - Max (mm ²) | 1.5 |

CONTINUUM PLUS 1.2 940 ST UGR DI SSA03 W

Item No: 2064636

Concord

Lifetime data

| | |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B50 | 89000 |

Physical data

| | |
|-----------------------------|----------------------------------|
| Housing colour | RAL 9016 - Traffic white / Bezel |
| IP rating | IP20 |
| IK rating | IK03 |
| Diffuser finish | Transparent |
| Diffuser material | PC Polycarbonate |
| Reflector finish | Not Applicable |
| Nominal Product Length (mm) | 1294 |
| Nominal Product Width (mm) | 56 |
| Nominal Product Height (mm) | 93 |
| Weight (kg) | 3.2 |

Packaging

| | |
|---------------------------------------|----------------|
| Product EAN number | 5025768646364 |
| Packaging single length / height (cm) | 139.0 |
| Packaging single width (cm) | 11.7 |
| Packaging single depth (cm) | 14.7 |
| DUN14 (inner) | 05025768646364 |
| Units per outer package | 1 |
| Packaging outer length / height (cm) | 139.0 |
| Packaging outer width (cm) | 11.7 |
| Packaging outer depth (cm) | 14.7 |

Safety data

| | |
|----------------------------------|------|
| Glow Wire Test (°C) | 650 |
| Optimal operating condition (°C) | 1-25 |