

# CONTINUUM PLUS 1.5 940 ST OPAL D DALI B

Item No: 2064684

Concord



CONTINUUM PLUS 1.5 940 ST OPAL D DALI B is a linear luminaire for surface, ceiling recessed or suspended mounting, with 3 meter pre-wiring and complete with end caps and suspension cables, direct light distribution, compact and minimalist design, ideal for offices, meeting rooms, corridors, education facilities, museums and libraries, black (RAL9005) finishing, extruded aluminium body, 1509x56x85mm dimensions, opal diffuser, 4000K (neutral white) colour temperature, total system power: 26.5W, total fixture output: 3650lm, luminaire efficacy: 138lm/W, colour rendering: Ra >90, LED Chromacity: 3 step MacAdam ellipse, lifespan: 89,000 hours L80B50, operating voltage: 220-240V / 50-60Hz, drive current: 625mA, electronic driver, DALI dimmable, Class I electrical protection, IP20, IK03, suitable for internal environment only.

## Technical Assets

### Dimensions (mm)



### Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam angle [°]	Beam angle [°]	Illuminance [lx]
0.5	1.23	0.71	90°	90°	9573
	1.31	E100	90°	708	652
1.0	2.45	0.71	90°	1396	1396
	2.62	E100	90°	1177	1177
1.5	3.68	0.71	90°	625	625
	3.92	E100	90°	517	517
2.0	4.90	0.71	90°	348	348
	5.23	E100	90°	281	281
2.5	6.13	0.71	90°	223	223
	6.54	E100	90°	181	181
3.0	7.36	0.71	90°	168	168
	7.85	E100	90°	137	137

Distance [m] Cone diameter [m] Illuminance [lx]  
 — C0 - C180 (Half beam angle: 105.2°)  
 — C90 - C270 (Half beam angle: 101.6°)



# CONTINUUM PLUS 1.5 940 ST OPAL D DALI B

Item No: 2064684

## Concord

### General data

Product name	CONTINUUM PLUS 1.5 940 ST OPAL D DALI B
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended, Ceiling surface mounting, Ceiling recessed mounting
Built in presence detector	NONE
Fixture rating	Enclosed
General application	Office, Education, Retail
Operating temperature range (°C)	1°C...+25°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 years

### Optical data

Fixture luminous flux (lm)	3650
Luminaire efficacy (lm/W)	138
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

### Electrical data

Emergency type	
Total power consumption (W)	26.5
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	6.1
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Minimum dimming level (%)	1
Drive current (mA)	625
Inrush Current (A)	35
Inrush Duration (µs)	170
Energy Efficiency Class (A->G) of contained light source	B, C (more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 13A C Breaker	28
Max. products per 16A C Breaker	35
Max. products per 20A C Breaker	45
Max. products per 10A B Breaker	13
Max. products per 13A B Breaker	17
Max. products per 16A B Breaker	21
Max. products per 20A B Breaker	27
Connectable conductor cross section - Min (mm <sup>2</sup> )	0.75
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5

# CONTINUUM PLUS 1.5 940 ST OPAL D DALI B

Item No: 2064684

Concord

## Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B50	89000

## Physical data

Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK03
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	Not Applicable
Nominal Product Length (mm)	1509
Nominal Product Width (mm)	56
Nominal Product Height (mm)	85
Weight (kg)	4.0

## Packaging

Product EAN number	5025768646845
Packaging single length / height (cm)	161.0
Packaging single width (cm)	11.7
Packaging single depth (cm)	14.7
DUN14 (inner)	05025768646845
Units per outer package	1
Packaging outer length / height (cm)	161.0
Packaging outer width (cm)	11.7
Packaging outer depth (cm)	14.7

## Safety data

Glow Wire Test (°C)	650
Optimal operating condition (°C)	1-25