

CONTINUUM PLUS 3.6 940 ST UGR D DALI EM B

Item No: 2064857

Concord



CONTINUUM PLUS 3.6 940 ST UGR D DALI EM B is a linear luminaire for surface, ceiling recessed or suspended mounting, with 3 meter pre-wiring and complete with end caps and suspension cables, direct light distribution, compact and minimalist design, ideal for offices, meeting rooms, corridors, education facilities, museums and libraries, black (RAL9005) finishing, extruded aluminium body, 3609x56x85mm dimensions, prismatic diffuser combined with lenses, 4000K (neutral white) colour temperature, total system power: 69W, total fixture output: 9450lm, luminaire efficacy: 137lm/W, colour rendering: Ra >90, LED Chromacity: 3 step MacAdam ellipse, lifespan: 89,000 hours L80B50, operating voltage: 220-240V / 50-60Hz, drive current: 1500mA, electronic driver, DALI dimmable, 3-hours LiFePO4 integrated DALI Self Test emergency, Class I electrical protection, IP20, IK03, suitable for internal environment only.

Technical Assets

Dimensions (mm)



Photometrics

| Distance [m] | Cone diameter [m] | Beam diameter [m] | Beam diameter [ft] | Illuminance [lx] |
|--------------|-------------------|-------------------|--------------------|---|
| 0.5 | 0.71 0.73 | 0.71 0.73 | 2.33 2.39 | 2009 809 35.3° 35.1° E.C.O. 35.1° 779 |
| 1.0 | 1.42 1.46 | 1.42 1.46 | 4.66 4.78 | 7542 2518 35.3° 35.1° E.C.O. 35.1° 1945 |
| 1.5 | 2.13 2.19 | 2.13 2.19 | 6.99 7.17 | 3283 896 35.3° 35.1° E.C.O. 35.1° 854 |
| 2.0 | 2.83 2.92 | 2.83 2.92 | 9.32 9.54 | 1536 654 35.3° 35.1° E.C.O. 35.1° 498 |
| 2.5 | 3.54 3.65 | 3.54 3.65 | 11.65 11.97 | 1175 332 35.3° 35.1° E.C.O. 35.1° 371 |
| 3.0 | 4.25 4.38 | 4.25 4.38 | 13.97 14.34 | 816 234 35.3° 35.1° E.C.O. 35.1° 276 |

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 72.0°)
 — C90 - C270 (Half beam angle: 70.0°)



CONTINUUM PLUS 3.6 940 ST UGR D DALI EM B

Item No: 2064857

Concord

General data

| | |
|----------------------------------|--|
| Product name | CONTINUUM PLUS 3.6 940 ST UGR D DALI EM B |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Suspended, Ceiling surface mounting, Ceiling recessed mounting |
| Built in presence detector | NONE |
| Fixture rating | Enclosed |
| General application | Office, Education, Retail |
| Operating temperature range (°C) | 1°C...+25°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC002892 |
| Warranty | 5 years |

Optical data

| | |
|-----------------------------------|---------------|
| Fixture luminous flux (lm) | 9450 |
| Luminaire efficacy (lm/W) | 137 |
| Correlated colour temperature (k) | 4000 |
| Light colour | Neutral White |
| CRI (Ra) | 90 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Distribution type | Symmetric |
| Glare control | < 19 |
| Photobiological Risk Group | RG1 |
| Luminous flux (emergency) (lm) | 540 |

Electrical data

| | |
|--|-----------------------------|
| Emergency mode | Maintained |
| Emergency type | |
| Emergency duration (h) | 3 |
| Total power consumption (W) | 69 |
| Supply current (A) | 0.197 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.98 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 10 |
| Electrical protection | Class I |
| Control gear required | No |
| Control gear type | LED driver constant current |
| Dimmable | Yes |
| Dimming method | DALI-2 |
| Minimum dimming level (%) | 1 |
| Drive current (mA) | 1500 |
| Inrush Current (A) | 35 |
| Inrush Duration (µs) | 170 |
| Energy Efficiency Class (A->G) of contained light source | B |
| Nominal Frequency (Hz) | 50/60Hz |
| LED Flickering Rate | Ultra low (5% or less) |
| Max. products per 10A C Breaker | 30 |
| Max. products per 13A C Breaker | 38 |
| Max. products per 16A C Breaker | 46 |
| Max. products per 20A C Breaker | 58 |
| Max. products per 10A B Breaker | 18 |
| Max. products per 13A B Breaker | 23 |
| Max. products per 16A B Breaker | 28 |
| Max. products per 20A B Breaker | 35 |
| Connectable conductor cross section - Min (mm ²) | 0.75 |
| Connectable conductor cross section - Max (mm ²) | 1.5 |

CONTINUUM PLUS 3.6 940 ST UGR D DALI EM B

Item No: 2064857

Concord

Lifetime data

| | |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B50 | 89000 |

Physical data

| | |
|-----------------------------|----------------------|
| Housing colour | RAL 9005 - Jet black |
| IP rating | IP20 |
| IK rating | IK03 |
| Diffuser finish | Transparent |
| Diffuser material | PC Polycarbonate |
| Reflector finish | Not Applicable |
| Nominal Product Length (mm) | 3609 |
| Nominal Product Width (mm) | 56 |
| Nominal Product Height (mm) | 85 |
| Weight (kg) | 10.4 |

Packaging

| | |
|---------------------------------------|----------------|
| Product EAN number | 5025768648573 |
| Packaging single length / height (cm) | 371.0 |
| Packaging single width (cm) | 11.7 |
| Packaging single depth (cm) | 14.7 |
| DUN14 (inner) | 05025768648573 |
| Units per outer package | 1 |
| Packaging outer length / height (cm) | 371.0 |
| Packaging outer width (cm) | 11.7 |
| Packaging outer depth (cm) | 14.7 |

Safety data

| | |
|----------------------------------|------|
| Glow Wire Test (°C) | 650 |
| Optimal operating condition (°C) | 1-25 |