

# Solstice 200 2250lm 940 SSC01D Surface Mounted

Item No: 2070204

**Concord**




SylSmart®



The Solstice 200 2250lm 940 SSC Surface Mounted is a high efficient DALI dimmable downlight luminaire, Colour rendering index Ra>90, Colour temperature: 4000K Neutral White, Class II, Overall dimensions: dia 196mm, height 196mm.

## Technical Assets


### Dimensions (mm)



### Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [in]	Illuminance [lx]
0.5	0.78	507	20.1"	5973
1.0	1.57	507	20.1"	1489
1.5	2.35	507	20.1"	664
2.0	3.14	507	20.1"	373
2.5	3.92	507	20.1"	239
3.0	4.70	507	20.1"	166

Distance [m] Cone diameter [m] Illuminance [lx]  
C0 - C180 (Half beam angle: 76.2°)



# Solstice 200 2250lm 940 SSC01D Surface Mounted

Item No: 2070204

**Concord**

## General data

Product name	Solstice 200 2250lm 940 SSC01D Surface Mounted
Technology	LED
Cap/Base	N/A
Housing	Aluminium, PC Polycarbonate
Mount	Ceiling surface mounting
Built in presence detector	NONE
General application	Hospitality, Office, Retail
Operating temperature range (°C)	5°C...+35°C
Performance ambient temperature Tq (°C)	35
Virtual assistant compatibility	N/A
ETIM Class	EC001744
E-number FI	4170414
Warranty	5 years

## Optical data

Fixture luminous flux (lm)	2250
Luminaire efficacy (lm/W)	132
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	90
Colour Consistency (SDCM)	3
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

## Electrical data

Emergency type	
Total power consumption (W)	17
Supply current (A)	1
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart Standalone (SSC)
Drive current (mA)	450
Inrush Current (A)	20
Inrush Duration (µs)	220
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	50
Max. products per 13A C Breaker	40
Max. products per 16A C Breaker	51
Max. products per 20A C Breaker	50
Max. products per 10A B Breaker	18
Max. products per 13A B Breaker	80
Max. products per 16A B Breaker	28
Max. products per 20A B Breaker	40
Connectable conductor cross section - Min (mm <sup>2</sup> )	0.5
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5

# Solstice 200 2250lm 940 SSC01D Surface Mounted

Item No: 2070204

# Concord

## Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B50	89000
Lifespan L90 B50	42000

## Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK02
Diffuser finish	Diffuse
Diffuser material	PC Polycarbonate
Reflector finish	High-gloss
Nominal Product Height (mm)	196
Nominal Product Diameter (mm)	196
Max. Lamp Diameter (mm) - D	196
Weight (kg)	2.94

## Packaging

Product EAN number	5025768702046
Packaging single length / height (cm)	27.5
Packaging single width (cm)	27.5
Packaging single depth (cm)	26.5
DUN14 (inner)	05025768702046
Units per outer package	1
Packaging outer length / height (cm)	27.5
Packaging outer width (cm)	27.5
Packaging outer depth (cm)	26.5

## Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	5-35