



# Rocks IP65 32KLM 840 AISLE DALI

Item No: 2825409

# Concord

## General data

Product name	Rocks IP65 32KLM 840 AISLE DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Suspended
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
ETIM Class	EC001716
E-number FI	4327144
Warranty	5 years

## Optical data

Fixture luminous flux (lm)	32500
Luminaire efficacy (lm/W)	183
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Distribution type	Asymmetric
Glare control	< 22
Photobiological Risk Group	RG1

## Electrical data

Emergency type	
Total power consumption (W)	178
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.97
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	8
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Drive current (mA)	690
Inrush Current (A)	17
Inrush Duration (µs)	1500
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	6
Max. products per 13A C Breaker	8
Max. products per 16A C Breaker	9
Max. products per 20A C Breaker	12
Max. products per 10A B Breaker	6
Max. products per 13A B Breaker	8
Max. products per 16A B Breaker	9
Max. products per 20A B Breaker	12

## Lifetime data

Lifespan L70 B50	120000
Lifespan L80 B50	105000
Lifespan L80 B20	91000

# Rocks IP65 32KLM 840 AISLE DALI

Item No: 2825409

**Concord**

## Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser material	PC Polycarbonate
Reflector finish	Matt
Nominal Product Length (mm)	481
Nominal Product Width (mm)	446
Nominal Product Height (mm)	86
Weight (kg)	4.68

## Packaging

Product EAN number	5025768254095
Packaging single length / height (cm)	53.5
Packaging single width (cm)	49.5
Packaging single depth (cm)	20.0
DUN14 (inner)	05025768254095
Units per outer package	1
Packaging outer length / height (cm)	53.5
Packaging outer width (cm)	49.5
Packaging outer depth (cm)	20.0

## Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-30-50