

SYL-LIGHTER II 220 21W NW DALI

Item No: 3031846

General data

Product name	SYL-LIGHTER II 220 21W NW DALI
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Fixture rating	Enclosed
Environment	Interior
General application	Hospitality
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4270285
E-number SE	7470959
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2102
Luminaire efficacy (lm/W)	100
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	5
Beam Angle (°)	74
Distribution type	Symmetric
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	21
Lamp power factor	0.96
Electrical protection	Class II
Control gear required	Yes
Control gear type	Other
Control gear mounting	Remote
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
Drive current (mA)	600
Inrush Current (A)	26
Inrush Duration (µs)	151
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	31
Max. products per 13A C Breaker	43
Max. products per 16A C Breaker	53
Max. products per 20A C Breaker	66
Max. products per 10A B Breaker	19
Max. products per 13A B Breaker	26
Max. products per 16A B Breaker	32
Max. products per 20A B Breaker	40

Lifetime data

Lifespan L70 B50	50000
------------------	-------

SYL-LIGHTER II 220 21W NW DALI

Item No: 3031846

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	Other
Nominal Product Height (mm)	60
Nominal Product Diameter (mm)	220
Weight (kg)	0.757

Packaging

Product EAN number	8711971318460
Packaging single length / height (cm)	25.3
Packaging single width (cm)	25.3
Packaging single depth (cm)	7.2
DUN14 (inner)	18711971318460
Units per outer package	12
Packaging outer length / height (cm)	52.4
Packaging outer width (cm)	52.6
Packaging outer depth (cm)	23.8

Safety data

Glow Wire Test (°C)	850
---------------------	-----