



GIOTTO 335 3000K SURFACE 1-10V EMERGENCY

Item No: 3034821

SYLVANIA


PROTM



Ambient and decorative round, surface mounted LED bulkhead luminaire. White robust polycarbonate body with opal diffuser, 2225lm, 21.6W, 104lm/W, 3000K, CRI 80, 1-10V dimmable, integral 3 hour maintained emergency, 120,000 hours lumen maintenance (L70:B50). Drive current: 600mA, IP44, IK10, Class I, 220-240V.

Technical Assets

Dimensions (mm)




Photometrics

0.5	1.58	50°	50°	2745	201
1.0	3.15	50°	50°	696	51
1.5	4.73	50°	50°	305	23
2.0	6.30	50°	50°	172	13
2.5	7.88	50°	50°	110	8
3.0	9.45	50°	50°	75	5

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (half beam angle: 115.2°)



GIOTTO 335 3000K SURFACE 1-10V EMERGENCY

Item No: 3034821

SYLVANIA

General data

Product name	GIOTTO 335 3000K SURFACE 1-10V EMERGENCY
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
Built in presence detector	NONE
Environment	Indoor
General application	Hospitality, Logistics & Industry
Operating temperature range (°C)	1°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2225
Luminaire efficacy (lm/W)	104
Correlated colour temperature (k)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Adjustable chromaticity	N
Beam Angle (°)	120
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	80
Luminous flux (emergency) (lm)	144

Electrical data

Emergency type	
Emergency duration (h)	3
Total power consumption (W)	21.6
Primary Supply/Product voltage - min (V)	198.0
Primary Supply/Product voltage - max (V)	264.0
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	Yes
Dimming method	1-10V (Analogue)
Drive current (mA)	600
Inrush Current (A)	5
Inrush Duration (µs)	50
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	52
Max. products per 16A C Breaker	85
Max. products per 20A C Breaker	104
Max. products per 10A B Breaker	31
Max. products per 16A B Breaker	50
Max. products per 20A B Breaker	62
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	2.5

Lifetime data

Lifespan L70 B10	120000
Lifespan L80 B50	120000
Lifespan L90 B50	74500

GIOTTO 335 3000K SURFACE 1-10V EMERGENCY

Item No: 3034821



Physical data

Housing colour	White
IP rating	IP44
IK rating	IK10
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Height (mm)	110
Nominal Product Diameter (mm)	335
Weight (kg)	1.5

Packaging

Product EAN number	8711971348214
Packaging single length / height (cm)	35.7
Packaging single width (cm)	35.7
Packaging single depth (cm)	10.6
DUN14 (inner)	08711971348214
Units per outer package	1
Packaging outer length / height (cm)	35.7
Packaging outer width (cm)	35.7
Packaging outer depth (cm)	10.6

Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	1-25