

REFLED SUPERIA RETRO ES50 345LM 827 36° SL

Item No: 0029950

SYLVANIA




- Premium performance professional LED GU10 range with the same look and feel of traditional halogen GU10 lamp
- Recreates backlight effect similar to halogen dichroic lamps
- Full glass design - means no colours clashing between lamp and fixture
- Very long lifetime of up to 25,000 hours
- COOLFIT functionality – ensures overheat and over temperature protection
- High switching cycles: >100,000
- High colour rendering: CRI80
- Non dimmable
- Warranty: 5 Years

Technical Assets

Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.31 0.32	0.31 0.32	2637 1224 1237
1.0	0.63 0.63	0.63 0.63	709 309 309
1.5	0.94 0.95	0.94 0.95	315 137 137
2.0	1.26 1.26	1.26 1.26	177 77 77
2.5	1.57 1.56	1.57 1.56	113 68 68
3.0	1.88 1.89	1.88 1.89	79 54 54

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 26.9°)
 — C90 - C270 (Half beam angle: 34.9°)



REFLED SUPERIA RETRO ES50 345LM 827 36° SL

Item No: 0029950

SYLVANIA

General data

Product name	REFLED SUPERIA RETRO ES50 345LM 827 36° SL
Technology	LED
Watt (Rated) (W)	4
Cap/Base	GU10
Fixture rating	Open
General application	Education, Hospitality, Museums & Galleries, Office, Residential & Consumer, Retail
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740684
Warranty	5 years

Optical data

Useful luminous flux (Φ_{use})	345
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Luminous Intensity (cd)	700
Beam Angle (°)	36
Lumen maintenance at end of nominal life (%)	70

Electrical data

Power consumption (W)	4
Wattage (W)	4
Equivalent watt (W)	50
Starting time (max) (s)	<0.5
Warm-up time to 60% of full light (max) (s)	<1
Lamp power factor	0.55
No. Of switching cycles before premature failures	>100000
Dimmable	No
Inrush Current (A)	3.4
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	13
Max. products per 16A C Breaker	21
Max. products per 20A C Breaker	26

Lifetime data

Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

Physical data

Nominal Product Length (mm)	54
Nominal Product Diameter (mm)	50
Weight (kg)	0.048

REFLED SUPERIA RETRO ES50 345LM 827 36° SL

Item No: 0029950



Packaging

Product EAN number	5410288299501
Packaging single length / height (cm)	5.1
Packaging single width (cm)	5.1
Packaging single depth (cm)	6.7
DUN14 (inner)	15410288299508
Units per inner package	6
Packaging inner length / height (cm)	11.0
Packaging inner width (cm)	16.4
Packaging inner depth (cm)	8.1
DUN14 (outer)	25410288299505
Units per outer package	60
Packaging outer length / height (cm)	58.6
Packaging outer width (cm)	18.6
Packaging outer depth (cm)	18.7

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	None