



VELITE WALL ADJUSTABLE WHITE UP AND DOWN 3000K

Item No: 0047814


SYLVANIA




Adjustable surface wall up and down light luminaire, white aluminium, 290lm, 5W, 58lm/W, 3000K, Driver Current: 700mA, CRI:80+, 220-240V, IP54, IK05, 30.000 hrs (L70), 108x108x109mm

Technical Assets

Dimensions (mm)



Photometrics



General data

Product name	VELITE WALL ADJUSTABLE WHITE UP AND DOWN 3000K
Technology	LED
Housing	Aluminium
Mount	Wall surface mounted
Environment	External
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+45°C
ETIM Class	EC002892
E-number FI	4579192
E-number SE	7703128
Warranty	3 years

Optical data

Fixture luminous flux (lm)	290
Luminaire efficacy (lm/W)	58
LOR (%)	100
Correlated colour temperature (k)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Adjustable chromaticity	N
Beam Angle (°)	94
Distribution type	Direct
Photobiological Risk Group	RG1

VELITE WALL ADJUSTABLE WHITE UP AND DOWN 3000K

Item No: 0047814

SYLVANIA

Electrical data

Total power consumption (W)	5
Supply current (A)	0.03
Lamp power factor	0.7
THD (at 230 V, 50 Hz, full load, at 100% dimming level) \leq xx.x %	10
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Drive current (mA)	700
Inrush Current (A)	10.3
Inrush Duration (μ s)	300
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	High (>40%)
Max. products per 10A C Breaker	38
Max. products per 13A C Breaker	35
Max. products per 16A C Breaker	35
Max. products per 20A C Breaker	30

Lifetime data

Lifespan L70 B50	30000
Lifespan L80 B50	20000
Lifespan L90 B50	12000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP54
IK rating	IK05
Diffuser finish	Transparent
Diffuser material	Glass
Nominal Product Length (mm)	108
Nominal Product Width (mm)	108
Nominal Product Height (mm)	109
Weight (kg)	0.803

Packaging

Product EAN number	5410288478142
Packaging single length / height (cm)	14.6
Packaging single width (cm)	14.6
Packaging single depth (cm)	14.6
DUN14 (inner)	15410288478149
Units per outer package	8
Packaging outer length / height (cm)	60.6
Packaging outer width (cm)	32.0
Packaging outer depth (cm)	16.9

Safety data

Glow Wire Test ($^{\circ}$ C)	850
Optimal operating condition ($^{\circ}$ C)	-20-45