

# START Waterproof Single 1500 IP65 MW 4000lm 840

Item No: 0067957


**SYLVANIA**



Start Waterproof, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing, Polycarbonate diffuser, 3950lm, 36W, 110lm/W, 4000K, drive current 1050mA, MW On/Off, CRI80, IP65, IK08, Class I, nominal average life (h):50000, 1578mm x 84mm x 75mm ,energy class: A++ A+ A, D-mark

## Technical Assets


### Dimensions (mm)



### Photometrics

Distance [m]	Cone diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	1.29 1.37	0.71 0.80	543 540 559
1.0	2.78 2.75	1.41 1.60	137 138 140
1.5	4.17 4.10	2.12 2.40	603 603 60
2.0	5.57 5.47	2.83 3.20	339 339 35
2.5	6.96 6.83	3.54 4.00	211 211 22
3.0	8.35 8.20	4.25 4.80	151 151 16

Distance [m]      Cone diameter [m]      Illuminance [lx]  
 — C0 - C180 (Half beam angle: 107.6°)  
 — C90 - C270 (Half beam angle: 108.6°)



# START Waterproof Single 1500 IP65 MW 4000lm 840

Item No: 0067957

**SYLVANIA**

## General data

Product name	START Waterproof Single 1500 IP65 MW 4000lm 840
Technology	LED
Housing	PC Polycarbonate
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4306955
Warranty	5 years

## Optical data

Fixture luminous flux (lm)	3950
Luminaire efficacy (lm/W)	110
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	< 25
Photobiological Risk Group	RG0

## Electrical data

Total power consumption (W)	36
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
Drive current (mA)	1050
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	20
Max. products per 13A C Breaker	30
Max. products per 16A C Breaker	40
Max. products per 20A C Breaker	50
Max. products per 10A B Breaker	16
Max. products per 13A B Breaker	24
Max. products per 16A B Breaker	32
Max. products per 20A B Breaker	40

## Lifetime data

Lifespan L70 B50	60000
Lifespan L70 B20	60000
Lifespan L70 B10	60000
Lifespan L80 B50	60000
Lifespan L80 B20	60000
Lifespan L80 B10	60000
Lifespan L90 B50	59000
Lifespan L90 B20	53000
Lifespan L90 B10	50000

# START Waterproof Single 1500 IP65 MW 4000lm 840

Item No: 0067957

**SYLVANIA**

## Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1578
Nominal Product Width (mm)	84
Nominal Product Height (mm)	75
Weight (kg)	2.08

## Packaging

Product EAN number	5410288679570
Packaging single length / height (cm)	167.2
Packaging single width (cm)	8.8
Packaging single depth (cm)	8.4
DUN14 (inner)	05410288679570
Units per outer package	1
Packaging outer length / height (cm)	167.2
Packaging outer width (cm)	8.8
Packaging outer depth (cm)	8.4

## Safety data

Glow Wire Test (°C)	850
Optimal operating condition (°C)	-20-40
Dry applications use only	No