

Concord Beacon 3000k SM Wide o/b Dim Black

Item No: 2062485


Concord



Simple and slick integral design with no driver box and without any visible screws New technology utilization for improved performance Extremely precise light beams due to the high-quality lenses ø80mm die-cast aluminium body, Fix beam angle: 55°, Textured black finishing colour Light color temperature: 3000K, warm light System power: 18W, Fixture lumen output: 1525lm, efficacy: 85lm/W, Ra97 typical, LED chromacity: 2 step MacAdam ellipse LED source (SDCM2), IR/UV free light source without heat radiation Operating voltage 220-240V / 50-60Hz, dimmable via on-board potentiometer, Surface mounting with surface mounting base. Electrical protection: Class II. Degree of protection: IP20, suitable for indoor environment only Horizontal rotation: 355°, vertical tilt: 90° Nominal product dimensions: D.80x200mm 5 years warranty. Suitable for ceiling surface mounting, and wall surface mounting

Technical Assets


Dimensions (mm)



Photometrics

| Distance [m] | Cone diameter [m] | Beam diameter [m] | Beam diameter [m] | Illuminance [lx] |
|--------------|-------------------|-------------------|-------------------|------------------|
| 0.5 | 0.52 0.53 | 0.071 0.090 | 0.071 0.090 | 2071 2096 |
| 1.0 | 1.05 1.06 | 0.143 0.180 | 0.143 0.180 | 749 734 |
| 1.5 | 1.57 1.58 | 0.214 0.270 | 0.214 0.270 | 502 501 |
| 2.0 | 2.09 2.10 | 0.286 0.360 | 0.286 0.360 | 377 368 |
| 2.5 | 2.61 2.63 | 0.357 0.450 | 0.357 0.450 | 303 299 |
| 3.0 | 3.14 3.15 | 0.429 0.540 | 0.429 0.540 | 250 250 |

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 55.4°)
 — C90 - C270 (Half beam angle: 55.2°)



Concord Beacon 3000k SM Wide o/b Dim Black

Item No: 2062485

Concord

General data

| | |
|----------------------------------|--|
| Product name | Concord Beacon 3000k SM Wide o/b Dim Black |
| Technology | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Mount | Ceiling surface mounting, Wall surface mounted |
| Built in presence detector | NONE |
| Fixture rating | Enclosed |
| General application | Museums & Galleries, Retail, Hospitality |
| Operating temperature range (°C) | -10°C...+35°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC001744 |
| Warranty | 5 years |

Optical data

| | |
|-----------------------------------|------------|
| Fixture luminous flux (lm) | 1525 |
| Luminaire efficacy (lm/W) | 85 |
| LOR (%) | 100 |
| Correlated colour temperature (k) | 3000 |
| Light colour | Warm White |
| CRI (Ra) | 97 |
| Colour Variation Initial (SDCM) | SDCM2 |
| Luminous Intensity (cd) | 1525 |
| Beam Angle (°) | 55 |
| Distribution type | Symmetric |
| Photobiological Risk Group | RG1 |

Electrical data

| | |
|--|-----------------------------|
| Emergency type | |
| Total power consumption (W) | 18 |
| Supply current (A) | 0.082 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.9 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 7.9 |
| Electrical protection | Class II |
| Control gear type | LED driver constant current |
| Dimmable | Yes |
| Dimming method | Onboard pot |
| Minimum dimming level (%) | 1 |
| Drive current (mA) | 500 |
| Inrush Current (A) | 5 |
| Inrush Duration (µs) | 50 |
| Energy Efficiency Class (A->G) of contained light source | F |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 31 |
| Max. products per 13A C Breaker | 65 |
| Max. products per 16A C Breaker | 85 |
| Max. products per 20A C Breaker | 104 |
| Max. products per 10A B Breaker | 31 |
| Max. products per 13A B Breaker | 39 |
| Max. products per 16A B Breaker | 50 |
| Max. products per 20A B Breaker | 62 |

Lifetime data

| | |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B50 | 100000 |
| Lifespan L90 B50 | 56000 |

Concord Beacon 3000k SM Wide o/b Dim Black

Item No: 2062485

Concord

Physical data

| | |
|-----------------------------|----------------------|
| Housing colour | RAL 9005 - Jet black |
| IP rating | IP20 |
| IK rating | IK02 |
| Diffuser finish | Other |
| Diffuser material | PMMA Acrylic |
| Reflector finish | Not Applicable |
| Nominal Product Length (mm) | 200 |
| Nominal Product Width (mm) | 80 |
| Nominal Product Height (mm) | 250 |
| Weight (kg) | 1.2 |

Packaging

| | |
|---------------------------------------|----------------|
| Product EAN number | 5025768624850 |
| Packaging single length / height (cm) | 30.5 |
| Packaging single width (cm) | 13.5 |
| Packaging single depth (cm) | 20.5 |
| DUN14 (inner) | 05025768624850 |
| Units per outer package | 1 |
| Packaging outer length / height (cm) | 30.5 |
| Packaging outer width (cm) | 13.5 |
| Packaging outer depth (cm) | 20.5 |

Safety data

| | |
|----------------------------------|--------|
| Glow Wire Test (°C) | 650 |
| Optimal operating condition (°C) | -10-35 |
| Dry applications use only | Yes |