

SYISMART SALVADOR 2016 SSC

Item No: V960012

SYLVANIA



The Salvador Series 2000 DALI controller seamlessly integrates up to 16 wired DALI drivers into the SylSmart Standalone system. When integrated, DALI luminaires appear as luminaires in the SylSmart Standalone network. The SylSmart Salvador 2016 supports industry standards such as DALI D4i, DALI DT6, and DALI DT8.

Technical Assets

Photometrics

General data

Product name	SYISMART SALVADOR 2016 SSC
Technology	Electronic Device
Type of accessory	Control
Virtual assistant compatibility	N/A
ETIM Class	EC000533
Warranty	5 years

Electrical data

Primary Supply/Product voltage - min (V)	100.0
Primary Supply/Product voltage - max (V)	277.0
Dimmable	Yes
Dimming method	DALI-2
Max. drive current (mA)	70
Drive current - Range (mA)	/ 70mA
Inrush Current (A)	20
Nominal Frequency (Hz)	50/60Hz

Physical data

IP rating	IP20
Nominal Product Length (mm)	106
Nominal Product Width (mm)	67
Nominal Product Height (mm)	28
Weight (kg)	0.12

Packaging

Packaging single length / height (cm)	14.0
Packaging single width (cm)	7.0
Packaging single depth (cm)	3.5
Units per outer package	1
Packaging outer length / height (cm)	14.0
Packaging outer width (cm)	7.0
Packaging outer depth (cm)	3.5