

Sylbay Gen II EM Kit Standard

Item No: 0040027




Sylbay Gen II EM Kit Standard provides a simple conversion of High Bay fitting with a high performance self-contained LED emergency luminaire KIT suitable for open areas, delivering 3 hours rated emergency output. Self testing with DALI monitoring capability. Supplied with all mounting accessories

Technical Assets

Photometrics

| Distance [m] | Cone diameter [m] | Beam diameter [m] | Beam angle [°] | Illuminance [lx] |
|--------------|-------------------|-------------------|----------------|------------------|
| 0.5 | 1.45 | 0.07 | 88.4° | 299 |
| 1.0 | 2.90 | 0.14 | 88.4° | 75 |
| 1.5 | 4.35 | 0.21 | 88.4° | 33 |
| 2.0 | 5.80 | 0.28 | 88.4° | 19 |
| 2.5 | 7.25 | 0.35 | 88.4° | 12 |
| 3.0 | 8.70 | 0.42 | 88.4° | 8 |

Distance [m] Cone diameter [m] Beam diameter [m] Beam angle [°] Illuminance [lx]
 C0 - C180 (Half beam angle: 110.8°)



Sylbay Gen II EM Kit Standard

Item No: 0040027

SYLVANIA

Informacion General

| | |
|---------------------|-------------------------------|
| Nombre del producto | Sylbay Gen II EM Kit Standard |
| Tecnología | Módulo de emergencia |
| Aplicación | Logística e industria |
| ETIM | EC002472 |
| Garantía | 3 años |

Datos ópticos

| | |
|--------------------------------|-----|
| Lúmenes | 200 |
| CRI (Ra) | 75 |
| Grupo de riesgo fotobiológico | RG1 |
| Luminous flux (emergency) (lm) | 200 |

Datos eléctricos

| | |
|------------------------------|----------|
| Emergency duration (h) | 3 |
| Tensión de alimentación mín. | 220 |
| Tensión de alimentación máx. | 240 |
| Factor de potencia | 0.44 |
| Protección eléctrica | Clase II |

Datos físicos

| | |
|------------------|--------|
| Acabado de color | Blanco |
| Protección IP | IP65 |
| Protección IK | IK03 |
| Peso (kg) | 1.1 |

Empaquetado

| | |
|--------------------------------------|----------------|
| Código EAN | 5410288400273 |
| Largo del embalaje individual (cm) | 32.5 |
| Ancho del embalaje individual (cm) | 32.5 |
| Alto del embalaje individual (cm) | 12.5 |
| DUN14 (inner) | 05410288400273 |
| Cantidad de unidades por caja | 1 |
| Largo / alto del embalaje outer (cm) | 32.5 |
| Ancho del embalaje outer (cm) | 32.5 |
| Profundidad del embalaje outer (cm) | 12.5 |