

PANEL 50-240V EMERGENCY KIT

Code article 0047595

SYLVANIA



50-240V emergency accessory pack for LED light sources, includes 3 x 4Ah D Cell Ni-Cd, 2.4W power consumption, LED current limit 240mA, Battery current limit 960mA, 24 hour charge period, mains frequency 50Hz, trickle charge current 80-130mA nominal. Do not use with surface mounting kits with panels.

Atouts techniques

Photométrie

Données générales

| | |
|----------------------|--|
| Nom du produit | PANEL 50-240V EMERGENCY KIT |
| Technologie | Accessory |
| Corps | Acier |
| Montage | Installation en saillie au plafond |
| Environnement | Intérieur |
| Application générale | Education, CHR (Café- Hôtel-Restaurant), Bureaux, Commerce |
| Classe ETIM | EC000471 |
| Numéro virtuel SE | 7016422 |
| Garantie | 2 ans |

Caractéristiques électriques

| | |
|---------------------------------|----------|
| Secours durée (hrs) | 3 |
| Actuel (A) | 0.02 |
| Facteur de puissance lampe | 0.9 |
| Classe de protection électrique | Classe 1 |

Données physiques

| | |
|---------------|------|
| Longueur (mm) | 400 |
| Largeur (mm) | 90 |
| Hauteur (mm) | 40 |
| Poids (kg) | 1.55 |

Emballage

| | |
|--------------------------------------|----------------|
| Code EAN | 5410288475950 |
| Longueur simple de l'emballage (cm) | 46.0 |
| Largeur simple de l'emballage (cm) | 12.5 |
| Hauteur emballage unitaire (cm) | 5.0 |
| DUN14 (inner) | 15410288475957 |
| Unités par emballage extérieur | 1 |
| Packaging outer length / height (cm) | 47.0 |
| Packaging outer width (cm) | 33.0 |
| Profondeur boîte extérieure (cm) | 36.0 |