

Pixo Line Driver Multipower 600 Black

Code article 0007866

SYLVANIA


PROTM



Pixo Line is a linear track system, adds flexibility to any space due the variety of product optionsOffers an easy installation with two separate modulesPush-in/push-out mechanism with GR6d-15 connectorCompatible with Zhaga Book 14Constant current 350mA -1050mA LED in-track driver with GR6d-15 connector for LED light modules, polycarbonate bodyClip holder and fixing screw included in the driver box, black finishing colour, max. system power: 56W, operating voltage: 220-240V / 50-60HzDriver module should be combined with suitable LED module. Multipower driver module with 8 power settings meet all installation needs with one single product selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA)Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrackElectrical protection: Class I. Degree of protection: IP20, suitable for indoor environment onlyLight modules should be combined with suitable in-track driversNominal product dimensions: L.672mmx32mmx31mm. This driver can be combined with Pixo Line 1500, and Pixo Line 900 (max.29W-600mA)

Atouts techniques

Dimensions (mm)



Photométrie

Pixo Line Driver Multipower 600 Black

Code article 0007866

SYLVANIA

Données générales

Nom du produit	Pixo Line Driver Multipower 600 Black
Technologie	Driver
Montage	Track mounting
General application	Hospitality, Museums & Galleries, Office, Retail
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC002710
Numéro virtuel FI	4279417
Warranty	5 ans

Données optiques

Couleur de lumière	N/A
Photobiological Risk Group	Not applicable

Caractéristiques électriques

Consommation électrique totale (W)	56
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
No. Of switching cycles before premature failures	>100000
Dimmable	No
Dimming method	N/A
Min. drive current (mA)	350
Max. drive current (mA)	1050
Drive current - Range (mA)	350mA / 1050mA
Courant d'appel (A)	42
Inrush Duration (µs)	168
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	15
Max. products per 16A C Breaker	24
Max. products per 10A B Breaker	9
Max. products per 16A B Breaker	14
Mains surge immunity (differential mode -> L-N) (kV)	1

Données physiques

Housing colour	Black
IP rating	IP20
IK rating	IK03
Longueur (mm)	672
Largeur (mm)	31
Nominal Product Height (mm)	31.5
Poids (kg)	0.36

Pixo Line Driver Multipower 600 Black

Code article 0007866

SYLVANIA

Emballage

Product EAN number	5410288078663
Longueur simple de l'emballage (cm)	68.0
Largeur simple de l'emballage (cm)	5.0
Packaging single depth (cm)	3.7
DUN14 (inner)	15410288078660
Units per outer package	20
Packaging outer length / height (cm)	70.0
Packaging outer width (cm)	27.0
Packaging outer depth (cm)	17.0

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40