

Resisto 1200 IP66 3450-6050lm 840 MW ON/OFF

Code article 0010460

SYLVANIA


PROTM



Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform light appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time, IP66, IK08, Class I, SDCM<3, 4000K, CRI>80, non-dimmable, 3450 / 4350 / 5100 / 6050lm (4 different steps selectable with DIP switches), 19 / 24 / 28 / 33.5W, 182 / 181 / 182 / 181lm/W depends on setting, 100.000hrs L80B10 lifespan, 1200 x 89 x 88mm (L x W x H) dimensions, 1.41kg weight, operating temperature range from -20 to +40°C. D-mark, ENEC certification. Supplied with integrated Microwave On/Off sensor.


Atouts techniques

Dimensions (mm)



Photométrie

Distance (m)	Cone diameter (m)	Beam angle (°)	Half beam angle (°)	Illuminance (lx)
0.5	1.27 1.40	51° 51°	25.5° 25.5°	4814 346
1.0	2.54 2.79	51° 51°	25.5° 25.5°	1183 137
1.5	3.81 4.19	51° 51°	25.5° 25.5°	513 51
2.0	5.08 5.59	51° 51°	25.5° 25.5°	256 29
2.5	6.35 6.96	51° 51°	25.5° 25.5°	158 13
3.0	7.62 8.38	51° 51°	25.5° 25.5°	109 10



Resisto 1200 IP66 3450-6050lm 840 MW ON/OFF

Code article 0010460



Données générales

Nom du produit	Resisto 1200 IP66 3450-6050lm 840 MW ON/OFF
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Montage	Ceiling surface mounting, Wall surface mounted
Built in presence detector	MICROWAVE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Numéro virtuel FI	4357228
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	6050
Luminaire efficacy (lm/W)	182
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	110
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

Caractéristiques électriques

Emergency type	
Consommation électrique totale (W)	33.5
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.96
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	8
Electrical protection	Class I
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Courant d'appel (A)	16.6
Inrush Duration (µs)	231
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	36
Max. products per 13A C Breaker	47
Max. products per 16A C Breaker	57
Max. products per 20A C Breaker	72
Max. products per 10A B Breaker	22
Max. products per 13A B Breaker	28
Max. products per 16A B Breaker	34
Max. products per 20A B Breaker	43
Connectable conductor cross section - Min (mm²)	0.75
Connectable conductor cross section - Max (mm²)	2.5

Resisto 1200 IP66 3450-6050lm 840 MW ON/OFF

Code article 0010460



Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B50	100000
Lifespan L80 B20	100000
Lifespan L80 B10	100000
Lifespan L90 B50	77000

Données physiques

Housing colour	RAL 7035 - Light grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Frosted
Diffuser material	PC Polycarbonate
Longueur (mm)	1200
Largeur (mm)	89
Nominal Product Height (mm)	88
Poids (kg)	1.41

Emballage

Product EAN number	5410288104607
Longueur simple de l'emballage (cm)	151.0
Largeur simple de l'emballage (cm)	10.3
Packaging single depth (cm)	8.8
DUN14 (inner)	15410288104604
Units per outer package	6
Packaging outer length / height (cm)	122.5
Packaging outer width (cm)	28.0
Packaging outer depth (cm)	22.0

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-20-40