

ToLEDo SUPERIA T5 AC 4FT 2400LM 840

Code article 0028031

SYLVANIA



50,000 hours average rated lifetime (L70 F50) Last 2.5 times longer than 28W 1149mm fluorescent tri-phosphor T5 lamp
High switching cycles - 200,000X High lumen efficacy - 150lm/W
Omni-directional light distribution and wide beam angle
Minimum and maximum operating temperature: -20°C to 50°C
Glass construction and polycarbonate end-caps
Only suitable for direct mains (AC 220-240V) operation
Ideal for factories, parking lots, supermarkets, department stores, schools and offices
Not suitable for operation with electronic/ECG or magnetic/CCG ballasts

Atouts techniques

Photométrie

Données générales

Nom du produit	ToLEDo SUPERIA T5 AC 4FT 2400LM 840
Technologie	LED
Puissance (nominale) (W)	16
Cap/Base	G5
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
Numéro virtuel FI	4740762
Warranty	5 ans

Données optiques

Flux lumineux utile (nominal) (lm)	2400
Température de couleur (K)	4000
Couleur de lumière	Cool White
IRC (Ra)	80
Maintien du flux à la fin de la durée de vie nominale (lm)	70

Caractéristiques électriques

Power consumption (W)	16
Wattage (W)	16
Heure de démarrage (max) (s)	<0.5
Temps de préchauffage jusqu'à 60 % de la pleine lumière (max) (s)	<2
Lamp power factor	0.9
No. Of switching cycles before premature failures	>200000
Dimmable	No

Durée de vie

Average life (Nominal) (h)	50000
Durée de vie moyenne (nominale) (h)	50000

Données physiques

Poids (kg)	0.138
------------	-------

ToLEDo SUPERIA T5 AC 4FT 2400LM 840

Code article 0028031



Emballage

Product EAN number	5410288280318
Longueur simple de l'emballage (cm)	116.5
Largeur simple de l'emballage (cm)	1.8
Packaging single depth (cm)	1.8
DUN14 (inner)	15410288280315
Units per outer package	10
Packaging outer length / height (cm)	121.8
Packaging outer width (cm)	15.6
Packaging outer depth (cm)	8.0

Sécurité

Consignes de nettoyage en cas de bris	Not applicable
Lampe à objectif spécial	No
Ne convient pas à l'éclairage résidentiel	Yes
Safety message	Suitable for totally enclosed fixture